

RANA Linear Recessed - Louvre+Prismatic Optic

RANA LINEAR R 3KLM NW LOUV+PRI

0052352



Product features

- Ceiling recessed LED Linear luminaire with Louvre + Micro Prismatic Optic, Dimensions: 1154mm x 90mm x 91mm, Direct, White Body, Neutral White LED (4000K), 3250lm, 27W, 120lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse), Low LED Flicker (+/-5%), UGR<19, L90B10 at 50,000 hours, Electric Class1, Glow Wire Test 850°C, Can be covered with building insulation of Glass wool type




PRODUCT OVERVIEW

Product name	RANA LINEAR R 3KLM NW LOUV+PRI
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Environment	Internal
General application	Office, Hospitality, Retail, Education
ETIM Class	EC002892
Warranty	5 years
Useful luminous flux (Fuse)	3250
Fixture luminous flux (lm)	3250
Luminaire efficacy (lm/W)	120.37
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	27
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288523521

RANA Linear Recessed - Louvre+Prismatic Optic
RANA LINEAR R 3KLM NW LOUV+PRI
0052352

PHOTOMETRY



TECHNICAL DRAWINGS

