



### Features

• 60,000 hours average rated lifetime (L70 F50). Last 3 times longer than 49W 1449mm fluorescent tri-phosphor T5 lamp. High switching cycles – 200,000X. High lumen efficacy -156lm/W. Omni-directional light distribution and wide beam angle. Minimum and maximum operating temperature: -20°C to 50°C. Glass construction and polycarbonate end-caps. Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast. Works only with compatible electronic ballasts. Ideal for factories, parking lots, supermarkets, department stores, schools and offices.

### Product Overview

Product name	TOLEDO SUPERIA T5 HO 5FT 4050LM 830
Technology	LED
Watt (Rated) (W)	26
E-number FI	4740610
E-number SE	8293583
Colour temperature (K)	3000
CRI (Ra)	80
Wattage (W)	26
Product EAN number	5410288295138
Warranty	5 years

### Data table

#### GENERAL DATA

Product name	TOLEDO SUPERIA T5 HO 5FT 4050LM 830
Technology	LED
Watt (Rated) (W)	26
Performance ambient temperature Tq (°C)	25

## TOLEDO SUPERIA T5 HO 5FT 4050LM 830 0029513

E-number FI	4740610
E-number SE	8293583
Warranty	5 years

### OPTICAL DATA

Luminous flux (Rated) (lm)	4050
Colour temperature (K)	3000
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

### ELECTRICAL DATA

Wattage (W)	26
Starting time (max) (s)	0.5
Current (A)	0.35
Primary Supply/Product voltage - min (V)	60.0
Lamp power factor	0.92
Control gear required	No
kWh per 1000 hours burning time	29

### LIFETIME DATA

Average life (Rated) (h)	60000
--------------------------	-------

### PHYSICAL DATA

Nominal Product Diameter (mm)	1449
Weight (kg)	0.174

### PACKAGING

Single packaging type	Carton
Product EAN number	5410288295138
Packaging single width (cm)	1.8
Packaging single depth (cm)	1.8
DUN14 (outer)	15410288295135

TOLEDO SUPERIA T5 HO 5FT 4050LM 830  
0029513

Packaging outer length / height (cm)	152.0
--------------------------------------	-------

## SAFETY DATA

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No
Safety message	Suitable for totally enclosed fixture