



### Features

• 60,000 hours average rated lifetime (L70 F50). Last 3 times longer than 49W 1449mm fluorescent tri-phosphor T5 lamp. High switching cycles – 200,000X. High lumen efficacy -162lm/W. Omni-directional light distribution and wide beam angle. Minimum and maximum operating temperature: -20°C to 50°C. Glass construction and polycarbonate end-caps. Not suitable for direct mains (AC 220-240V) or magnetic/CCG ballast. Works only with compatible electronic ballasts. Ideal for factories, parking lots, supermarkets, department stores, schools and offices.

### Product Overview

Product name	TOLEDO SUPERIA T5 HO 5FT 4200LM 840
Technology	LED
Watt (Rated) (W)	26
E-number FI	4740611
E-number SE	8293584
Colour temperature (K)	4000
CRI (Ra)	80
Wattage (W)	26
Product EAN number	5410288295145
Warranty	5 years

### Data table

#### GENERAL DATA

Product name	TOLEDO SUPERIA T5 HO 5FT 4200LM 840
Technology	LED
Watt (Rated) (W)	26
Performance ambient temperature Tq (°C)	25

## TOLEDO SUPERIA T5 HO 5FT 4200LM 840 0029514

E-number FI	4740611
E-number SE	8293584
Warranty	5 years

### OPTICAL DATA

Luminous flux (Rated) (lm)	4200
Colour temperature (K)	4000
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

### ELECTRICAL DATA

Wattage (W)	26
Starting time (max) (s)	0.5
Current (A)	0.35
Primary Supply/Product voltage - min (V)	60.0
Lamp power factor	0.92
Control gear required	No

### LIFETIME DATA

Average life (Rated) (h)	60000
--------------------------	-------

### PHYSICAL DATA

Nominal Product Diameter (mm)	1449
Weight (kg)	0.174

### PACKAGING

Single packaging type	Carton
Product EAN number	5410288295145
Packaging single width (cm)	1.8
Packaging single depth (cm)	1.8
DUN14 (outer)	15410288295142
Packaging outer length / height (cm)	152.0

## SAFETY DATA

---

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No
Safety message	Suitable for totally enclosed fixture