

SYLBAY LED 4000K 37KLM WIDE 1-10V PIR 0039276















Features

 Specification industrial high bay luminaire, robust and durable, slim design, high output and efficiency, lightweight, aluminium housing with shatter-resistant polycarbonate lens optic, 39,613 lumens, 276W, 144lm/W, 4000K, 2100mA (x2), CRI 80, wide beam optic, 1-10V dimmable, integral PIR sensor with daylight/occupancy detection, IP66, IK08, (LxWxH) 665x375x105mm, 3 step MacAdam ellipse, 8.9kg, aluminium finish, Class 1, 220-240V, integrated LED, energy class: A++, A+, A.

Product Overview

| Product name | SYLBAY LED 4000K 37KLM WIDE 1-10V PIR |
|-----------------------------------|---------------------------------------|
| Technology | LED |
| Housing | Aluminium |
| Mount | Ceiling surface mounting |
| Fixture rating | Enclosed |
| Environment | Internal |
| General application | Logistics & Industry |
| ETIM Class | EC001716 |
| E-number FI | 4306927 |
| Fixture luminous flux (lm) | 39613 |
| Luminaire efficacy (lm/W) | 144 |
| LOR (%) | 100 |
| Correlated colour temperature (k) | 4000 |
| Light colour | Neutral White |
| CRI (Ra) | 80 |
| Colour Consistency (SDCM) | 3 |
| Beam Angle (°) | 80 |
| Photobiological Risk Group | RG1 |
| Total power consumption (W) | 276 |
| Electrical protection | Class I |
| Control gear type | Electronic ballast |




SYLBAY LED 4000K 37KLM WIDE 1-10V PIR

0039276

| Control gear mounting | Integral |
|-----------------------|------------------|
| Housing colour | Silver |
| IP rating | IP66 |
| IK rating | IK08 |
| Product EAN number | 5410288392769 |
| Warranty | 5 years |
| Dimming method | 1-10V (Analogue) |

Photometry



Technical drawings

