



Features

- Integrated LED highbay; Black aluminium housing; 26400Lm; 165 W; 160 Lm/W; 4000K; Drive current: 720mA; CRI 80; 55° beam angle; DALI dimmable; IP65; IK08; Lifespan L80:B20 92,000 hrs; (D x H) 370 x 163 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.


Product Overview

Product name	Sylvania Granit IP65 DALI 26400lm 840 MB
Technology	LED
Cap/Base	N/A
General application	Logistics & Industry
ETIM Class	EC001716
Fixture luminous flux (lm)	26400
Luminaire efficacy (lm/W)	160
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	55
Glare control	< 22
Photobiological Risk Group	RG1
Total power consumption (W)	165
Electrical protection	Class I
Dimmable	Yes
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL9017
IP rating	IP65


Sylvania Granit IP65 DALI 26400lm 840 MB
0039751

IK rating	IK08
Product EAN number	5410288397511
Warranty	5 years
Dimming method	DALI-2

Photometry



Technical drawings



Sylvania Granit IP65 DALI 26400lm 840 MB 0039751

Data table

GENERAL DATA

Product name	Sylvania Granit IP65 DALI 26400lm 840 MB
Technology	LED
Cap/Base	N/A
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
ETIM Class	EC001716
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	26400
Luminaire efficacy (lm/W)	160
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	55
Distribution type	Symmetric
Glare control	< 22
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	165
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	15
Electrical protection	Class I
Control gear required	No

Sylvania Granit IP65 DALI 26400lm 840 MB 0039751

No. Of switching cycles before premature failures	>100000
Dimmable	Yes
Dimming method	DALI-2
Drive current (mA)	720
Inrush Current (A)	58
Inrush Duration (µs)	198
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	10
Max. products per 13A C Breaker	12
Max. products per 16A C Breaker	16
Max. products per 20A C Breaker	20
Max. products per 10A B Breaker	6
Max. products per 13A B Breaker	8
Max. products per 16A B Breaker	10
Max. products per 20A B Breaker	12
Mains surge immunity (differential mode -> L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	6

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L80 B20	92000
Lifespan L90 B50	51000

PHYSICAL DATA

Housing colour	RAL9017
IP rating	IP65
IK rating	IK08
Nominal Product Height (mm)	163



Sylvania Granit IP65 DALI 26400lm 840 MB
0039751

Nominal Product Diameter (mm)	370
Weight (kg)	2.703

PACKAGING

Product EAN number	5410288397511
Packaging single length / height (cm)	40.0
Packaging single width (cm)	40.0
Packaging single depth (cm)	14.5
DUN14 (inner)	05410288397511
Units per outer package	1
Packaging outer length / height (cm)	40.0
Packaging outer width (cm)	40.0
Packaging outer depth (cm)	14.5

SAFETY DATA

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-30-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No