


Sylbay 4000K L6 47000LM AISLE DALI
0040315



Features

- Logistics and Industry modular high bay luminaire with aisle optics to provide necessary illumination for narrow areas. Twin body with 6 optical modules, 47400 lumens, 327W, 145lm/W, 4000K, CRI 80, aisle beam optic, DALI dimmable, 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK08, (LxWxH) 726x386x133mm, Mains + control cable of 2 meter.

Product Overview

Product name	Sylbay 4000K L6 47000LM AISLE DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC001716
Fixture luminous flux (lm)	47400
Luminaire efficacy (lm/W)	145
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Beam Angle (°)	30*60
Glare control	< 23
Photobiological Risk Group	RG1
Total power consumption (W)	327
Electrical protection	Class I

Sylbay 4000K L6 47000LM AISLE DALI 0040315

GENERAL DATA

Product name	Sylbay 4000K L6 47000LM AISLE DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-40°C...+50°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001716
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	47400
Luminaire efficacy (lm/W)	145
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Colour Consistency (SDCM)	3
Beam Angle (°)	30*60
Glare control	< 23
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	327
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.96

Sylbay 4000K L6 47000LM AISLE DALI 0040315

THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	5.1
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic ballast
Control gear mounting	Integral
Dimmable	Yes
Dimming method	DALI
Drive current (mA)	750
Inrush Current (A)	4.65
Inrush Duration (µs)	584
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	8
Max. products per 16A C Breaker	8
Max. products per 10A B Breaker	3
Max. products per 16A B Breaker	5

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L80 B20	120000
Lifespan L90 B10	52000

PHYSICAL DATA

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	726
Nominal Product Width (mm)	386
Nominal Product Height (mm)	133
Weight (kg)	8.07



Sylbay 4000K L6 47000LM AISLE DALI
0040315

PACKAGING

Product EAN number	5410288403151
Packaging single length / height (cm)	92.0
Packaging single width (cm)	47.5
Packaging single depth (cm)	27.0
DUN14 (inner)	05410288403151
Units per outer package	1
Packaging outer length / height (cm)	92.0
Packaging outer width (cm)	47.5
Packaging outer depth (cm)	27.0

SAFETY DATA

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-40-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No