

Features

- Logistics and Industry modular high bay luminaire with wide optics to provide homogenous light distribution for open space areas. Twin body with 4 optical modules, 31000 lumens, 205W, 156lm/W, 4000K, CRI 80, wide beam optic, DALI dimmable, 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK08, (LxWxH) 726x386x133mm, Mains + control cable of 2 meter.


Product Overview

Product name	Sylbay 4000K L4 32000LM WIDE DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
ETIM Class	EC001716
Fixture luminous flux (lm)	31000
Luminaire efficacy (lm/W)	156
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	3
Beam Angle (°)	75
Glare control	< 22
Photobiological Risk Group	RG1
Total power consumption (W)	205


Sylbay 4000K L4 32000LM WIDE DALI
0040310

Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral
Dimmable	Yes
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288403106
Warranty	5 years
Dimming method	DALI

Photometry



Technical drawings





Sylbay 4000K L4 32000LM WIDE DALI
0040310

Data table

GENERAL DATA

Product name	Sylbay 4000K L4 32000LM WIDE DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-40°C...+50°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001716
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	31000
Luminaire efficacy (lm/W)	156
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Colour Consistency (SDCM)	3
Beam Angle (°)	75
Glare control	< 22
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	205
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240

Sylbay 4000K L4 32000LM WIDE DALI 0040310

Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	5.1
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic ballast
Control gear mounting	Integral
Dimmable	Yes
Dimming method	DALI
Drive current (mA)	700
Inrush Current (A)	65
Inrush Duration (µs)	268
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	5
Max. products per 13A C Breaker	7
Max. products per 16A C Breaker	8
Max. products per 20A C Breaker	10
Max. products per 10A B Breaker	3
Max. products per 13A B Breaker	4
Max. products per 16A B Breaker	5
Max. products per 20A B Breaker	6

LIFETIME DATA

Lifespan L70 B50	120000
Lifespan L80 B20	120000
Lifespan L90 B10	52000

PHYSICAL DATA

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser material	PC Polycarbonate



Sylbay 4000K L4 32000LM WIDE DALI
0040310

Nominal Product Length (mm)	726
Nominal Product Width (mm)	386
Nominal Product Height (mm)	133
Weight (kg)	8.07

PACKAGING

Product EAN number	5410288403106
Packaging single length / height (cm)	92.0
Packaging single width (cm)	47.5
Packaging single depth (cm)	27.0
DUN14 (inner)	05410288403106
Units per outer package	1
Packaging outer length / height (cm)	92.0
Packaging outer width (cm)	47.5
Packaging outer depth (cm)	27.0

SAFETY DATA

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-40-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No