


START WATERPROOF 1200 HOUSING 2X 0047194



Features

- Luminaire, polycarbonate housing
- Single version, 1200mm
- Protection type IP65
- Luminous flux and light colour vary depending on LED tubes used
- To be used with T8 LED tubes
- Easy to install with stainless steel fixing brackets included for ceiling mounting
- Ideal for any industrial facilities, garages, car parks, workshops.

Product Overview

Product name	START WATERPROOF 1200 HOUSING 2X
Technology	LED
Cap/Base	2G13
Housing	PC Polycarbonate
Mount	Wall surface mounted
Light source included	Fixture without Lightsource
E-number FI	4357156
Fixture luminous flux (lm)	1
Luminaire efficacy (lm/W)	1
Light colour	N/A
Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable
Total power consumption (W)	0.1
Electrical protection	Class II
Control gear type	Not required
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288471945
Warranty	5 years

START WATERPROOF 1200 HOUSING 2X 0047194

Data table

GENERAL DATA

Product name	START WATERPROOF 1200 HOUSING 2X
Technology	LED
Cap/Base	2G13
Housing	PC Polycarbonate
Mount	Wall surface mounted
Operating temperature range (°C)	-20°C...+40°C
E-number FI	4357156
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	1
Luminaire efficacy (lm/W)	1
Light colour	N/A
Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable

ELECTRICAL DATA

Light source included	Fixture without Lightsource
Total power consumption (W)	0.1
Primary Supply/Product voltage - min (V)	220.0
Electrical protection	Class II
Control gear required	No
Control gear type	Not required
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	1
Max. products per 16A C Breaker	1
Connectable conductor cross section - Max (mm ²)	1.5

START WATERPROOF 1200 HOUSING 2X 0047194

LIFETIME DATA

Lifespan L70 B50	25000
------------------	-------

PHYSICAL DATA

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1280
Nominal Product Width (mm)	100
Weight (kg)	0.9

PACKAGING

Product EAN number	5410288471945
Packaging single width (cm)	9.7
Packaging single depth (cm)	4.4
DUN14 (outer)	15410288471942
Packaging outer length / height (cm)	133.0

SAFETY DATA

Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No