

## SylCircle DualTone

SYLCIRCLE IP44 1025LM 830/840 DUALTONE

0043497



### Product features

- Ceiling / wall luminaire with integrated LED. Perfect solution for hallways, circulation spaces or foyer. Even and uniform light distribution with a halo lighting effect on the wall surface. Body Size diameter 250mm. Besa mounting box compatible, hole distance 51mm. DualTone functionality enables switch between 3000K and 4000K colour temperatures. Power 12W, output 1025 lumens (4000k). Non-dimmable. IK03, IP44. Low maintenance with 30,000 hours LED life expectancy.




### PRODUCT OVERVIEW

Product name	SYLCIRCLE IP44 1025LM 830/840 DUALTONE
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
General application	Hospitality
ETIM Class	EC002892
Warranty	3 years
Useful luminous flux (Fuse)	1025
Fixture luminous flux (lm)	1025
Luminaire efficacy (lm/W)	85
Light colour	Amber White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	12
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	High (>40%)
Housing colour	White
IP rating	IP44
IK rating	IK03
Product EAN number	5410288434971


### PHOTOMETRY

## SylCircle DualTone SYLCIRCLE IP44 1025LM 830/840 DUAL TONE 0043497



Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	1.70 1.77	860 71 85
1.0	3.41 3.53	215 16 18
1.5	5.11 5.30	121 5 7
2.0	6.82 7.07	68 4
2.5	8.52 8.84	44 3 3
3.0	10.23 10.60	30 2 2

Distance [m] Cone diameter [m] Illuminance [lx]  
 — C0 - C180 (Half beam angle: 121.9°)  
 — C90 - C270 (Half beam angle: 119.2°)



Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	1.70 1.77	860 71 85
1.0	3.41 3.53	215 16 18
1.5	5.11 5.30	121 5 7
2.0	6.82 7.07	68 4
2.5	8.52 8.84	44 3 3
3.0	10.23 10.60	30 2 2

Distance [m] Cone diameter [m] Illuminance [lx]  
 — C0 - C180 (Half beam angle: 121.9°)  
 — C90 - C270 (Half beam angle: 119.2°)

### TECHNICAL DRAWINGS

