




## SylCircle DualTone SYLCIRCLE IP44 520LM 830/840 DUAL TONE 0043496




Distance [m]	Cone diameter [m]	E(0°) [lx]	E(C0) [lx]	E(C90) [lx]
0.5	1.76	607	60.4°	60.4°
1.0	3.52	152	60.4°	60.4°
1.5	5.28	55	60.4°	60.4°
2.0	7.04	31	60.4°	60.4°
2.5	8.80	20	60.4°	60.4°
3.0	10.56	14	60.4°	60.4°

Distance [m] Cone diameter [m]  
E(0°) E(C0) E(C90)  
C0-C180 (Half beam angle: 120.8°)

Distance [m]	Cone diameter [m]	E(0°) [lx]	E(C0) [lx]	E(C90) [lx]
0.5	1.76	607	60.4°	60.4°
1.0	3.52	152	60.4°	60.4°
1.5	5.28	55	60.4°	60.4°
2.0	7.04	31	60.4°	60.4°
2.5	8.80	20	60.4°	60.4°
3.0	10.56	14	60.4°	60.4°

Distance [m] Cone diameter [m]  
E(0°) E(C0) E(C90)  
C0-C180 (Half beam angle: 120.8°)



### TECHNICAL DRAWINGS

