

Data Sheet | Item Number: 734-230

Operating tool; made of insulating material; 1-way; white

<https://www.wago.com/734-230>



Color: ■ white

Technical data

Number of spacings	1 -times
--------------------	----------

Physical data

Depth	18.9 mm / 0.75 inches
Pin spacing	3.5/3.81 mm

Mechanical data

Suitable	for 734, 2734 Series
----------	----------------------

Material data

Color	white
Material group	I
Insulation material	Glass fiber-reinforced polyamide (PA66 GF)
Flammability class per UL94	HB
Fire load	0.006 MJ
Weight	0.2 g

Commercial data

Product Group	3 (Multi Conn. System)
eCl@ss 10.0	27-44-04-92
eCl@ss 9.0	27-44-04-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332703253
Customs tariff number	82055980000

Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Approvals / Certificates

Approvals for marine applications



Approval	Standard	Certificate Name
LR Lloyds Register	IEC 61984	96/20035 (E5)

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 734-230



CAD/CAE-Data

CAD data

2D/3D Models 734-230




CAE data

ZUKEN Portal 734-230



Installation Notes



Inserting a conductor via operating lever.