



Features

• LiFeSafe PRO MULTIFIX EX SUS EM3 NM/MT DA is a DALI addressable LED ceiling suspended exit sign complete with six ISO7010 legends: Left, Right, 2 x Up and 2 x Down. Maintained or Non-Maintained, 3Hr emergency duration. Maximum viewing distance 28m. 0 to +35°C operating temperature range. IK02, IP65, Class II electrical construction, 6-year warranty.

Product Overview

Product name	LIFESAFE PRO MULTIFIX EX SUS EM3 NM/MTDA
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Light source included	0038842
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
ETIM Class	EC001957
Fixture luminous flux (lm)	50
Luminaire efficacy (lm/W)	25
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	50
Luminous flux (emergency) (lm)	50
Electrical protection	Class II
Control gear type	LED driver constant current
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5410288388427

LIFESAFE PRO MULTIFIX EX SUS EM3 NM/MTDA 0038842

Warranty

6 years

Technical drawings

