

## Expospot 90 cardan square


EXPOSPOT 90 DUO HO RA90 3000K MB WHITE

2070097



### Product features

- Integrated LED double gimbal accent downlight, duo head, ideal for retail and display applications, die-cast aluminium body, passive cooling, beam angle: 44°, optics: aluminium reflector and lens combination, colour temperature: 3000K warm white, total system power: 73W, total fixture output: 2x3180lm, 87lm/W, LOR: 100%, colour rendering: Ra 90 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, electronic driver, non-dimmable, electrical protection: CLASS II, ingress protection rating: IP20, suitable for internal environment only, ceiling cut-out: 148x292mm, dimensions: 163x307x104mm, weight: 2.1kg.




### PRODUCT OVERVIEW

Product name	EXPOSPOT 90 DUO HO RA90 3000K MB WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	2 x 3180
Luminaire efficacy (lm/W)	87
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	44
Photobiological Risk Group	RG1
Total power consumption (W)	73
Electrical protection	Class II
Control gear type	Electronic ballast
Control gear mounting	Remote
Dimmable	No
Dimming method	N/A
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5025768700974

### PHOTOMETRY

## Expospot 90 cardan square EXPOSPOT 90 DUO HO RA90 3000K MB WHITE 2070097



Distance [m]	Cone diameter [m]	E(0°) [lx]	E(22.1°) [lx]	E(44.2°) [lx]
0.5	0.41	1401	221	550
1.0	0.81	350	55	14
1.5	1.22	156	25	6
2.0	1.62	68	11	3
2.5	2.03	30	5	1
3.0	2.44	14	3	0.5

Distance [m] Cone diameter [m]  
C0-C180 (Half beam angle: 44.2°)

### TECHNICAL DRAWINGS

