



Color: ■ yellow Similar to illustration

Technical data		
Suitable		for wire cross-section 0.75 ... 1.5 mm²
Marking method		Thermal transfer
Marking		plain
Delivery form		Roll
Delivery form configuration		1000 pcs/reel; 3 lines
Printing device		Smart Printer (thermal transfer printer)

Physical data	
Depth	0.22 mm
Marking surface	5 x 23 mm

Mechanical data	
Mounting type	Sliding on conductor
Smear resistance	in conjunction with 258-5005 Ink Ribbon

Material data	
Color	yellow
Material	Polyester
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	without adhesive
Halogen-free	Yes
Weight	165 g
Fire load	0 MJ



Environmental requirements	
Ambient temperature (operation)	-40 ... +150 °C
Relative humidity	40 ... 50 %

Commercial data	
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4066966423693
Customs tariff number	39219090000

Product Classification	
UNSPSC	55121612
ETIM 9.0	EC001530
ETIM 10.0	EC001530
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance
211-861/000-002

↓