



TEST CERTIFICATE

Product certificate K-0222949-1



Issued 2025-04-01

Replaces --

Page 1 of 2

Concealed flushing cisterns

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Hansgrohe SE

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline

BRL-K620 "Flushing cisterns" dated 15-09-2019.

Which covers the requirements of

EN 14055: 2010 + A1: 2015 "WC and urinal flushing cisterns" June 2015.

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.
Sir Winston Churchillaan 273
P.O.Box 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
info@kiwa.com
www.kiwa.com

Company
Hansgrohe SE
Austraße 5-9
77761 SCHILTACH
Germany
Tel. +49 7836 51-0
info@hansgrohe.com
www.hansgrohe.com



Certification process
consists of initial and
regular assessment of:

- quality system
- product

Concealed flushing cisterns

PRODUCT SPECIFICATION

The products mentioned below belong to this certificate;

Concealed flushing cisterns with nominal flush volume of 6 Litres

Model **HG iFrame universal Concealed Cistern 112 WH WC;**

Concealed flushing cistern incorporated in freestanding WC Frame R015467 Prosys 120; with interrupted device, Dual Flush 6/3L incorporated with:

- Float valve : Oliveira & Irmao Azor Latplus
- Flush mechanism : Oliveira & Irmao Val Ain 120D MEC;

Code no. **01022180**

MARKING

The Kiwa®-mark products are marked with the wordmark "KIWA".

Place of the mark:

- the float valve : -on the body;
- the cistern: -on the left- right- under- or front side or on the inside above the maximum water level.

Compulsory specifications:

Manufacturers mark or logo

- the float valve: -on the body;
- the cistern: -on the left- right- under- or front side or on the inside above the maximum water level
- reference to European Standard EN 14055 (if applicable);

Method of marking:

- indelible;
- visible after assembly;
- EN 14055 required marking (if applicable).

APPLICATION AND USE

Flushing cisterns (in combination with WC pans) are intended for use as flushing units connected to drinking water installations with a water temperature of maximum 30°C. Flushing cisterns using a nominal flush volume of 6 litres are intended for use in connection with WC-pans of the type 6A, according to guideline BRL-K 619.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Hansgrohe SE

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.