
Technical data sheet

AML3518 anchor rail, slot 16.5 mm, FS, unperforated

Item number: 1118226



Central C profile rail for cable routing, in conjunction with clamp clips with a hammerhead foot. Can also be used as suspension construction for cable support systems.

CE 16,5 H E30 E90

St Steel

FS Strip galvanised

Master data


Item number	1118226
Type	AML3518UP2000FS
Description 1	Profile rail
Description 2	unperforated, slot 16.5mm
Manufacturer	OBO
Dimension	2000x35x18
Material	Steel
Surface	Strip galvanised
Surface standard	DIN EN 10346
Smallest sales unit	2
Unit of quantity	Metre
Weight	90 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to-Gate	2,0187 kg CO2e / 1 Meter

Technical data sheet

AML3518 anchor rail, slot 16.5 mm, FS, unperforated

Item number: 1118226

Dimensions



Length	2,000 mm
Width	35 mm
Height	18 mm
Dimension L	2,000 mm

Technical data

Breakable	no
Type of perforation	Without
Version for	Single profile
Bundle	20 m
Maintain electrical functions	no
Material thickness	1.5 mm
With perforation	no
With toothing	no
Profile shape	C profile
ROHS-conformant	yes
Slot width	16.5 mm
Static value A	1.14 cm²
Static value Iy	0.49 cm⁴
Static value Iz	0.85 cm⁴
Static value Wy	0.44 cm³
Static value Wz	1.05 cm³