

Optix Recessed Sylvania 600x600 Medium Output
OPTIX RECESSED 600x600 2L 4000K ALU SSH
0044139



PRODUCT OVERVIEW

Product name	OPTIX RECESSED 600x600 2L 4000K ALU SSH
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
E-number FI	4276563
Warranty	5 years
Fixture luminous flux (lm)	3400
Luminaire efficacy (lm/W)	126
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 16
Photobiological Risk Group	RG1
Total power consumption (W)	27
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288441399

DATA TABLE

General data	
Product name	OPTIX RECESSED 600x600 2L 4000K ALU SSH
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel

Optix Recessed Sylvania 600x600 Medium Output

OPTIX RECESSED 600x600 2L 4000K ALU SSH

0044139

Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Performance ambient temperature Tq (°C)	25
E-number FI	4276563
Warranty	5 years

Optical data

Fixture luminous flux (lm)	3400
Luminaire efficacy (lm/W)	126
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 16
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	27
Primary Supply/Product voltage - min (V)	198.0
Lamp power factor	0.96
Electrical protection	Class I
Control gear type	LED driver constant current
Drive current (mA)	250
Inrush Current (A)	25
Inrush Duration (µs)	177
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Connectable conductor cross section - Min (mm²)	2.5
Connectable conductor cross section - Max (mm²)	2.5

Lifetime data

Lifespan L70 B50	120000
Lifespan L80 B20	107500
Lifespan L90 B10	48500

Physical data


Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	596
Nominal Product Width (mm)	596
Weight (kg)	5.0

Optix Recessed Sylvania 600x600 Medium Output
OPTIX RECESSED 600x600 2L 4000K ALU SSH
0044139

Packaging

Single packaging type	Carton
Product EAN number	5410288441399
Packaging single width (cm)	6.5
Packaging single depth (cm)	65.0
DUN14 (outer)	05410288441399
Packaging outer length / height (cm)	62.0

PHOTOMETRY



TECHNICAL DRAWINGS

