



Color: ■ yellow Similar to illustration

Technical data	
Suitable	for wire cross-section 2.5 ... 6 mm²
Marking method	Thermal transfer
Marking	plain
Delivery form	Roll
Delivery form configuration	1000 pcs/reel; 3 lines
Printing device	Smart Printer (thermal transfer printer)

Physical data	
Depth	0.22 mm
Marking surface	7 x 26 mm
Sheathed cable diameter	3.3 ... 4.9 mm

Mechanical data	
Mounting type	Sliding on conductor
Smear resistance	in conjunction with 258-5005 Ink Ribbon

Material data	
Color	yellow
Material	Polyester
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	without adhesive
Halogen-free	Yes
Weight	165 g
Fire load	0 MJ



Environmental requirements	
Ambient temperature (operation)	-40 ... +150 °C
Relative humidity	40 ... 50 %

Commercial data	
ETIM 8.0	EC001530
ETIM 7.0	EC001530
PU (SPU)	1 pcs
Country of origin	DE
GTIN	4066966424010
Customs tariff number	39219090000

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance
211-862/000-002

↓

1 Compatible Products
1.1 Optional Accessories
1.1.1 Marking
1.1.1.1 Marking device



Item No.: 258-5000
Thermal transfer printer; Smart Printer; for complete control cabinet marking; 300 dpi; With marking material