



Color: ■ yellow

Technical data	
Suitable	for wire cross-section 6 ... 16 mm ²
Marking method	Thermal transfer
Marking	plain
Delivery form	Roll
Delivery form configuration	1000 pcs/reel; 2 lines
Printing device	Smart Printer (thermal transfer printer)

Physical data	
Depth	0.22 mm
Sheathed cable diameter	5.9 ... 8.3 mm

Mechanical data	
Mounting type	Sliding on conductor
Smear resistance	in conjunction with 258-5005 Ink Ribbon

Material data	
Color	yellow
Material	Polyester
UV resistance	EN 60068-2-5:2010 Procedure B
Adhesive information	without adhesive
Halogen-free	Yes
Weight	165 g
Fire load	0 MJ



Environmental requirements	
Ambient temperature (operation)	-40 ... +150 °C
Relative humidity	40 ... 50 %

Commercial data	
ETIM 8.0	EC001530
ETIM 7.0	EC001530
PU (SPU)	1 pcs
Country of origin	DE
GTIN	4066966424027
Customs tariff number	39219090000

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance
211-863/000-002

↓

1 Compatible Products
1.1 Optional Accessories
1.1.1 Marking
1.1.1.1 Marking device



Item No.: 258-5000
Thermal transfer printer; Smart Printer; for complete control cabinet marking; 300 dpi; With marking material