


## 15PKG-3232: Straight coupling Gas 32x32



### Commercial information

The PVDF press fittings for gas differ in only one significant technical aspect compared to press fittings for sanitary and heating applications. The fittings have a special O-ring that is made from the HNBR and is resistant to gas. To make this difference visible, every pressure sleeve has a yellow band. The fittings for gas should never be used for sanitary applications or heating applications. Similarly, fittings for gas should only be used in combination with the yellow HENCO multilayer pipe for gas.

The Henco system for gas is only permitted in countries where a gas quality mark has been granted.

PVDF offers the user a unique combination of properties:

- Highly resistant to pressure and temperature
- Excellent mechanical strength
- Extreme flexibility: bending up to 10° is possible
- Highly resistant to chemicals and corrosion
- Embedding is possible without extra protection

#### Certificates

GASTEC, TSU, ROST

#### Applications

Gas



#### Solutions

Building installations, Industry, Oil & gas, Utility, Shipbuilding

## Technical characteristics

|                                    |  |                                  |                        |
|------------------------------------|--|----------------------------------|------------------------|
| Material connection 1              | Polyvinylidene fluoride (PVDF)                     | Bend radius                      | 0 Millimetre           |
| Material quality connection 1      | Polyvinylidene fluoride (PVDF) (expired)           | Outer pipe diameter connection 1 | 32 Millimetre          |
| Surface protection connection 1    | Untreated  | Wall thickness, connection 1     | 0.9 Millimetre         |
| Surface treatment connection 1     | Untreated  | Outer pipe diameter connection 2 | 32 Millimetre          |
| Material connection 2              | Polyvinylidene fluoride (PVDF)                     | Wall thickness, connection 2     | 0.9 Millimetre         |
| Material quality connection 2      | Polyvinylidene fluoride (PVDF) (expired)           | Zeta value                       | 1.7                    |
| Surface protection connection 2    | Untreated  | Length                           | 102 Millimetre         |
| Surface treatment connection 2     | Untreated  | Length of connection 1           | 51 Millimetre          |
| Shape                              | Straight   | Working length connection 1      | 15 Millimetre          |
| Reducing                           | ✗  | Length of connection 2           | 51 Millimetre          |
| Eccentric                          | ✗  | Working length connection 2      | 15.5 Millimetre        |
| System specific                    | ✓  | Wrench width                     | 0 Millimetre           |
| Connection 1                       | Press sleeve                                       | Wrench width union nut           | 0 Millimetre           |
| Contour code connection 1          | BE   | Tightening moment                | 0 0 Newtonmetre        |
| Connection 2                       | Press sleeve                                       | Medium temperature (continuous)  | -20 60 Degrees celsius |
| Contour code connection 2          | BE   | Max. operating pressure at 20 °C | 10 Bar                 |
| Main colour fitting                | Black  | Standard Dimension Ratio (SDR)   | 0                      |
| Material sealing                   | Hydrogenated acrylonitrile butadiene rubber (HNBR) |                                  |                        |
| With buffer stud                   | ✓  |                                  |                        |
| High tensile strength              | ✗  |                                  |                        |
| With thermal insulation            | ✗  |                                  |                        |
| Ring stiffness class               | Other  |                                  |                        |
| With sealing rings/gaskets         | ✓  |                                  |                        |
| Capped                             | ✗  |                                  |                        |
| With connection indicator          | ✗  |                                  |                        |
| With drain valve                   | ✗  |                                  |                        |
| With de-aerator                    | ✗  |                                  |                        |
| FM quality mark                    | ✗  |                                  |                        |
| LPCB quality mark                  | ✗  |                                  |                        |
| ULC quality mark                   | ✗  |                                  |                        |
| UL quality mark                    | ✗  |                                  |                        |
| DIN-CERTCO certificate             | ✗  |                                  |                        |
| VdS quality mark                   | ✗  |                                  |                        |
| With approval for TÜV              | ✗  |                                  |                        |
| DVGW quality mark for gas          | ✗  |                                  |                        |
| DVGW quality mark for water        | ✗  |                                  |                        |
| Certified according to NF 545      | ✗  |                                  |                        |
| KIWA certified                     | ✗  |                                  |                        |
| Gastec QA mark                     | ✓  |                                  |                        |
| KOMO certified                     | ✗  |                                  |                        |
| Type approval according to BBR/EKS | ✗  |                                  |                        |

## Related products

| Product code   | GTIN           | Description   | Image   |
|----------------|----------------|---|---|
| PRESSCHECK1432 | 05414764017665 | Henco Tool to control the accuracy of a pressing Ø14-32 |  |
| BE32           | 05414764017665 | Henco Jaws (universal) BE-Profile 32x3                  |  |