


## VISION SET 16: Vision set Ø 16 ( sleeve + 2 O-rings )



### Commercial information

Henco revision set contains 2 O-rings and sleeve

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 28 mm    |
| Length     | 37 mm    |
| Width      | 28 mm    |
| Net weight | 0.018 kg |

#### Certificates

QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, WRAS, KOMO, STF, GOST-R, TSU, EMI

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

|                                    |                                                |                                  |                        |
|------------------------------------|------------------------------------------------|----------------------------------|------------------------|
| Material connection 1              | Polyvinylidene fluoride (PVDF)                 | Bend radius                      | 0 Millimetre           |
| Material quality connection 1      | Polyvinylidene fluoride (PVDF) (expired)       | Outer pipe diameter connection 1 | 16 Millimetre          |
| Surface protection connection 1    | Untreated                                      | Length                           | 37 Millimetre          |
| Surface treatment connection 1     | Untreated                                      | Wrench width union nut           | 0 Millimetre           |
| Material connection 2              | Polyvinylidene fluoride (PVDF)                 | Medium temperature (continuous)  | -10 70 Degrees celsius |
| Material quality connection 2      | Polyvinylidene fluoride (PVDF) (expired)       | Max. operating pressure at 20 °C | 10 Bar                 |
| Surface protection connection 2    | Untreated                                      | Standard Dimension Ratio (SDR)   | 0                      |
| Surface treatment connection 2     | Untreated                                      |                                  |                        |
| Reducing                           | ✗                                              |                                  |                        |
| Eccentric                          | ✗                                              |                                  |                        |
| System specific                    | ✓                                              |                                  |                        |
| Connection 1                       | Insert (push-fitting)                          |                                  |                        |
| Main colour fitting                | White                                          |                                  |                        |
| Material sealing                   | Ethylene-propylene diene monomer rubber (EPDM) |                                  |                        |
| With buffer stud                   | ✗                                              |                                  |                        |
| Self-sealing                       | ✗                                              |                                  |                        |
| With thermal insulation            | ✗                                              |                                  |                        |
| Ring stiffness class               | Other                                          |                                  |                        |
| With sealing rings/gaskets         | ✓                                              |                                  |                        |
| Capped                             | ✗                                              |                                  |                        |
| With connection indicator          | ✗                                              |                                  |                        |
| With drain valve                   | ✗                                              |                                  |                        |
| With de-aerator                    | ✗                                              |                                  |                        |
| FM quality mark                    | ✗                                              |                                  |                        |
| LPCB quality mark                  | ✗                                              |                                  |                        |
| ULC quality mark                   | ✗                                              |                                  |                        |
| UL quality mark                    | ✗                                              |                                  |                        |
| VdS quality mark                   | ✗                                              |                                  |                        |
| With approval for TÜV              | ✗                                              |                                  |                        |
| DVGW quality mark for gas          | ✗                                              |                                  |                        |
| DVGW quality mark for water        | ✓                                              |                                  |                        |
| KIWA certified                     | ✓                                              |                                  |                        |
| Gastec QA mark                     | ✗                                              |                                  |                        |
| KOMO certified                     | ✓                                              |                                  |                        |
| Type approval according to BBR/EKS | ✗                                              |                                  |                        |