

## Expospot 90 cardan square

EXPOSPOT 90 TRIO HO RA90 3000K MB WHITE

2070105



### Product features

- Integrated LED triple gimbal accent downlight, trio head, ideal for retail and display applications, die-cast aluminium body, passive cooling, beam angle: 44°, optics: aluminium reflector and lens combination, colour temperature: 3000K warm white, total system power: 107W, total fixture output: 3x3180lm, 89lm/W, LOR: 100%, colour rendering: Ra 90 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, electronic driver, non-dimmable, electrical protection: CLASS II, ingress protection rating: IP20, suitable for internal environment only, ceiling cut-out: 148x422mm, dimensions: 163x437x104mm, weight: 2.75kg.




### PRODUCT OVERVIEW

Product name	EXPOSPOT 90 TRIO HO RA90 3000K MB WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	3 x 3180
Luminaire efficacy (lm/W)	89
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	44
Photobiological Risk Group	RG1
Total power consumption (W)	107
Electrical protection	Class II
Control gear type	Electronic ballast
Control gear mounting	Remote
Dimmable	No
Dimming method	N/A
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5025768701056

### PHOTOMETRY

## Expospot 90 cardan square EXPOSPOT 90 TRIO HO RA90 3000K MB WHITE 2070105



Distance [m]	Cone diameter [m]	E(0°) [lx]	E(C0) [lx]	E(44.2°) [lx]
0.5	0.41	1401	22.1°	950
1.0	0.81	350	22.1°	117
1.5	1.22	156	22.1°	46
2.0	1.62	68	22.1°	39
2.5	2.03	32	22.1°	29
3.0	2.44	18	22.1°	21

Distance [m] Cone diameter [m]  
C0 - C180 (Half beam angle 44.2°)

### TECHNICAL DRAWINGS

