

Concord

EXOSPOT 90 TRIO HO RA90 4000K NB WHITE 2070108



Features

- Integrated LED triple gimbal accent downlight, trio head, ideal for retail and display applications, die-cast aluminium body, passive cooling, beam angle: 26°, optics: aluminium reflector and lens combination, colour temperature: 4000K neutral white, total system power: 107W, total fixture output: 3x3570lm, 100lm/W, LOR: 100%, colour rendering: Ra 90 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, electronic driver, non-dimmable, electrical protection: CLASS II, ingress protection rating: IP20, suitable for internal environment only, ceiling cut-out: 148x422mm, dimensions: 163x437x104mm, weight: 2.75kg.

Product Overview

Product name	EXOSPOT 90 TRIO HO RA90 4000K NB WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Fixture luminous flux (lm)	3 x 3570
Luminaire efficacy (lm/W)	100
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG1
Total power consumption (W)	107
Electrical protection	Class II
Control gear type	Electronic ballast

Concord

EXPOSPOT 90 TRIO HO RA90 4000K NB WHITE 2070108

Control gear mounting

Remote

Housing colour

White

IP rating

IP20

IK rating

IK02


Product EAN number

5025768701087


Warranty

5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Concord

EXPOSPOT 90 TRIO HO RA90 4000K NB WHITE 2070108

Product name	EXPOSPOT 90 TRIO HO RA90 4000K NB WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	3 x 3570
Luminaire efficacy (lm/W)	100
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	107
Primary Supply/Product voltage - min (V)	220
Lamp power factor	0.95
Electrical protection	Class II
Control gear required	No
Control gear type	Electronic ballast
Control gear mounting	Remote
Drive current (mA)	900
Inrush Current (A)	58.2
Inrush Duration (µs)	250
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	E

Concord

EXPOSPOT 90 TRIO HO RA90 4000K NB WHITE 2070108

Nominal Frequency (Hz)	50/60Hz
------------------------	---------

Max. products per 10A C Breaker	7
---------------------------------	---

Max. products per 20A B Breaker	9
---------------------------------	---

LIFETIME DATA

Lifespan L70 B50	100000
------------------	--------

Lifespan L80 B20	100000
------------------	--------

Lifespan L90 B10	54500
------------------	-------

PHYSICAL DATA

Housing colour	White
----------------	-------

IP rating	IP20
-----------	------

IK rating	IK02
-----------	------

Nominal Product Length (mm)	437
-----------------------------	-----

Nominal Product Width (mm)	163
----------------------------	-----

Weight (kg)	2.75
-------------	------

Recessed Depth (mm)	104
---------------------	-----

PACKAGING

Single packaging type	Carton
-----------------------	--------

Product EAN number	5025768701087
--------------------	---------------

Packaging single width (cm)	30.0
-----------------------------	------

Packaging single depth (cm)	20.0
-----------------------------	------

DUN14 (outer)	05025768701087
---------------	----------------

Packaging outer length / height (cm)	50.0
--------------------------------------	------

SAFETY DATA

Special purpose lamp	No
----------------------	----

Dry applications use only	No
---------------------------	----

Suitable for household illumination	No
-------------------------------------	----