

Central plate data 2x RJ oblique output, gold coated

221-65400



Central plate for 2 RJ outlets, oblique model. The central plate has a transparent text field to which you can easily add your text and icons. Colour: gold coated.

Technical data

Central plate data 2x RJ oblique output, gold coated.



- Function: the central plate is clicked onto the adaptor 4.4
- Material finishing: polycarbonate (PC) + acrylic-styrene-acrylate (ASA)
- Colour: gold coated
- Colour RAL (approximately): 1000
- Colour NCS (approximately): NCS S 3020-Y
- Surface treatment: coated
- Text field: at the top, the central plate is equipped with a hinged, transparent window with label. Dimensions label: 9.5 x 42.4 mm
- Number of lenses: 0
- Type of fastening: click on
- Dismantling method: pull the central plate off the mechanism
- Minimum ambient temperature: -5 °C
- Maximum ambient temperature: 40 °C
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: the combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Fire safety:
 - all plastic components are self-extinguishing (comply with a filament test of 650°C)
 - all plastic components are halogen-free
- Dimensions of finishing: 45 x 45 mm (HxW)
- Dimensions (HxWxD): 44.5 mm x 44.7 mm x 8.6 mm
- Marking: CE