

ToLEDo Stick

ToLEDo Stick V4 470LM 827 E27 SL

0029558



Product features

- A bright, all-around lighting solution for living rooms, wall lights, ceiling lights, compact and decorative luminaires
- Quick and easy replacement of compact fluorescent, halogen or incandescent lamp
- 15,000H average rated life
- 85% energy savings compared to incandescent
- Last 50% longer and consume 45% less energy compared to compact fluorescent integrated lamps
- Omni-directional light distribution
- Non-dimmable



PRODUCT OVERVIEW

Product name	ToLEDo Stick V4 470LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	5.0
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740964
Warranty	3 years
Luminous flux (lm)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Wattage (W)	5.0
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288295589

DATA TABLE

General data

Product name	ToLEDo Stick V4 470LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	5.0
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C

ToLEDo Stick

ToLEDo Stick V4 470LM 827 E27 SL

0029558

Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740964
Warranty	3 years

Optical data

Luminous flux (lm)	470
Luminous flux (Rated) (lm)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	5.0
Equivalent watt (W)	40
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
No. Of switching cycles before premature failures	>50000
Dimmable	No
Inrush Current (A)	1.8
Inrush Duration (µs)	200
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	220
Max. products per 16A B Breaker	220

Lifetime data

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Height (mm)	115
Nominal Product Diameter (mm)	37
Weight (kg)	0.034

Packaging

Single packaging type	Carton
Product EAN number	5410288295589
Packaging single length / height (cm)	5.0
Packaging single width (cm)	5.0
Packaging single depth (cm)	12.3

ToLEDo Stick

ToLEDo Stick V4 470LM 827 E27 SL


0029558

DUN14 (outer)	15410288295586
Units per outer package	6
Packaging outer length / height (cm)	15.4
Packaging outer width (cm)	10.3
Packaging outer depth (cm)	13.7


Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS




ToLEDo Stick

ToLEDo Stick V4 470LM 827 E27 SL
0029558



SYLVANIA

0029558



5
kWh/1000h



2019/2015


ToLEDo Stick

ToLEDo Stick V4 470LM 827 E27 SL

0029558



0029558



5
kWh/1000h



2019/2015