

Splashproof roll-down shutter switch 10 A, mechanically locked and galvanically isolated, screw terminals, grey

700-35900

10 A
250 Vac



4 year warranty

This roll-down shutter switch is galvanically isolated and is equipped with two plates to switch the electric motor in either direction. On the left-hand key, the word 'stop' is imprinted at the top and the word 'start' is imprinted at the bottom. On the right-hand key, an upward-pointing arrow is imprinted at the top and a downward-pointing arrow is imprinted at the bottom. The switch is to be mounted in a splashproof mounting box. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in ammonia-rich environments. Colour combination: light grey with dark grey button.

- all connections terminals are located at the top of the base:



Technical data

Splashproof roll-down shutter switch 10 A, mechanically locked and galvanically isolated, screw terminals, grey.

- Function:
 - switch
 - block-shaped silver contacts (cadmium-free) in the form of a cross
- Maximum MCB rating: 16 A (limited by national installation rules)
- Colour: grey
- Colour combination: light grey with dark grey button
- Colour RAL (approximately): 7035
- Colour NCS (approximately): frame NCS S 1502 - B, button NCS S 3502 - B
- Surface treatment: coloured in mass
- Imprint indication: two keys with 'start', 'stop' and two arrows indelibly imprinted. On the left key, 'stop' is indicated at the top, 'start' at the bottom. On the right key, an arrow pointing upwards is indicated at the top, an arrow pointing downward at the bottom
- Number of lenses: 0
- Number of mechanisms: 1
- Material base insert:
 - ureumformaldehyde (UF) with high heat resistance
 - white RAL9010 (approximately)
- Material finishing: the switch/push button is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6)

- mm). The control button is made of rigid ABS
- Terminal wire connection: screw terminals
 - Terminals wire capacity: $2 \times 2.5 \text{ mm}^2$
 - Terminals with screw driver slot : every screw is fitted with a screwdriver slot that prevents the screwdriver from sliding off the screwhead
 - Terminal screw head: combination screwhead (screw PZ1 or slot $0.85 \times 5 \text{ mm}$)
 - Wire stripping length: 8 mm
 - Wiring space:
 - 21.9 mm wiring space under the mechanism
 - mechanism is held by 2 laterally positioned holders in the box
 - a snap connector holds the wired mechanism in place
 - Wire stripping length: 8 mm
 - Markings on the flush-mounting frame:
 - indelibly indicated at the rear side: stripping length and wiring diagram
 - indelibly indicated at the front side: terminals and switch symbol
 - Recess for indication led:
 - the base is provided with 2 rectangular recesses for an optional lighting unit
 - left recess (front view): optional lighting unit with wires can be clicked in
 - Hermetic seal: the function is designed to be mounted in a splashproof mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box (to be ordered separately)
 - Chemical resistance: tested and approved for use in environments with ammonia levels up to 20 ppm
 - Protection degree: IP55 for the combination of a function and a splashproof mounting box
 - Impact resistance: the combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of $-25 \text{ }^{\circ}\text{C}$ and a maximum temperature of $55 \text{ }^{\circ}\text{C}$
 - Certification marks: CEBEC, DEMKO, NF, ÖVE, VDE
 - Marking: CE

Wiring diagram

