Lumiance

INSET TREND 75 SW ES50 WH EX-LMP **3083500**



Features

• 75mm cut out. 2 x 30° Tilt. Round bezel.




Product Overview

| Product name | INSET TREND 75 SW ES50 WH EX-LMP |
|-----------------------|----------------------------------|
| Technology | LED/Halogen |
| Cap/Base | GU10 |
| Housing | Aluminium |
| Mount | Ceiling recessed mounting |
| Light source included | Fixture without Lightsource |
| Environment | Indoor |
| E-number SE | 7463875 |
| LOR (%) | Dependent on lamp |
| Light colour | N/A |
| Electrical protection | Class II |
| Housing colour | White |
| IP rating | IP23/20 |
| IK rating | IK02 |
| Product EAN number | 8711971835004 |
| Warranty | 3 years |

Lumiance

INSET TREND 75 SW ES50 WH EX-LMP **3083500**

Technical drawings



Data table

GENERAL DATA

| Product name | INSET TREND 75 SW ES50 WH EX-LMP |
|--------------|----------------------------------|
| Technology | LED/Halogen |
| Cap/Base | GU10 |
| Housing | Aluminium |
| Mount | Ceiling recessed mounting |
| Environment | Indoor |
| E-number SE | 7463875 |
| Warranty | 3 years |

OPTICAL DATA

| LOR (%) | Dependent on lamp |
|-------------------------|-------------------|
| Light colour | N/A |
| Adjustable chromaticity | N |

ELECTRICAL DATA

Lumiance

INSET TREND 75 SW ES50 WH EX-LMP

3083500

| Light source included | Fixture without Lightsource |
|--|-----------------------------|
| Primary Supply/Product voltage - min (V) | 220 |
| Electrical protection | Class II |
| Control gear required | No |
| Nominal Frequency (Hz) | 50/60Hz |

PHYSICAL DATA

| Housing colour | White |
|-----------------------------|---------|
| IP rating | IP23/20 |
| IK rating | IK02 |
| Nominal Product Length (mm) | 83 |
| Nominal Product Width (mm) | 83 |
| Weight (kg) | 0.25 |
| Recessed Depth (mm) | 100 |

PACKAGING

| Single packaging type | Carton |
|--------------------------------------|----------------|
| Product EAN number | 8711971835004 |
| Packaging single width (cm) | 11.0 |
| Packaging single depth (cm) | 7.0 |
| DUN14 (outer) | 18711971835001 |
| Packaging outer length / height (cm) | 14.0 |

SAFETY DATA

| Special purpose lamp | No |
|-------------------------------------|----|
| Dry applications use only | No |
| Suitable for household illumination | No |