


Concord

CONCORD BEACON 3000K SM MEDIUM DALI WHITE 2062545



Features

- Simple and slick integral design with no driver box and without any visible screws

New technology utilization for improved performance
Extremely precise light beams due to the high-quality lenses #80mm die-cast aluminium body, Fix beam angle: 36° , Textured white finishing colour Light color temperature: 3000K, warm light System power: 18W, Fixture lumen output: 1625lm, efficacy: 90lm/W, Ra97 typical, LED chromacity: 2 step MacAdam ellipse LED source (SDCM2), IR/UV free light source without heat radiation Operating voltage 220-240V / 50-60Hz, electronic driver, DALI dimmable Surface mounting with surface mounting base. Electrical protection: Class II. Degree of protection: IP20, suitable for indoor environment only Horizontal rotation: 355°, vertical tilt: 90° Nominal product dimensions: D.80mmx200mm 5 years warranty. Suitable for ceiling surface mounting, and wall surface mounting

Product Overview

Cap/Base	N/A
Mount	Ceiling surface mounting, Wall surface mounted
General application	Museums & Galleries, Retail, Hospitality
ETIM Class	EC001744
Luminaire efficacy (lm/W)	90
CRI (Ra)	97
Beam Angle (°)	36
Photobiological Risk Group	RG1
Total power consumption (W)	18
Control gear type	LED driver constant current
Dimmable	Yes
Minimum dimming level (%)	1

Concord

CONCORD BEACON 3000K SM MEDIUM DALI WHITE 2062545

IK rating

IK02


Warranty

5 years

Dimming method

DALI

Photometry



Technical drawings

