

1133600	DATA SHEET	
valid from: 2026-06-24	ÖLFLEX® SERVO 2XSLEY-JB	

Application

ÖLFLEX® SERVO 2XSLEY-JB are flexible cables, having special EMC-performance due to double shield, with low capacitance design and PVC sheath. They are designed for the European, North American and Canadian market. The cables are ideal suitable for three-phase motors of small, medium and large sizes operated by frequency converters. The cables are designed for use in dry, damp and wet conditions. They are suitable for free, non-continuously recurring movements without tensile load or compulsory guidance and also for fixed installation. The cables are suitable for outdoor use due to their black outer sheath. At room temperature they are widely resistant to acids, alkali-resistant and resistant to certain oils. Furthermore, the cables are flame retardant and self-extinguishing.

The version with earth-symmetrical construction (3+3) has a split protective conductor with a reduced overall cross-section.

This concentric conductor arrangement avoids to a large extent the high-frequency motor bearing currents which can lead to motor bearing damage, especially at high frequencies and long motor cables. The earthing concept for the earth-symmetrical version with the protective conductor splitted in thirds is composed of the defined cross-sections of the protective conductors and the screening braid. This design also improves the electromagnetic compatibility (EMC) of the entire drive system.

Application range:

Connection cable between frequency converter and motor: paper industry, chemical industry, heavy industry

USE acc. to : External interconnection or internal wiring of electronic equipment.

USE acc. to : Internal or external interconnection with or without mechanical load conditions.

Design

Design	acc. to UL: AWM Style 2570, UL 758 and acc. to CSA C22.2 No. 210 and based on HD 603 S1 + A3 and VDE 0250-1
Certification	 : AWM Style 2570, UL 758 (File No. E63634)  : AWM II A/B (File No. E63634)
	EN 13501-6 and EN 50575 Classification of fire behaviour (article/dimension range see www.lappkabel.com/cpr)
Conductor	fine wire strands of bare copper acc. to IEC 60228 resp. EN IEC 60228, class 5
Insulation	XLPE
Core identification code	acc. to HD 308 S2 resp. VDE 0293-308
Cable assembly	4 cores: twisted together in one layer 3+3 cores: twisted concentrically, protective conductor divided into three, positioned in the interstices
Screen	double screening with aluminium-coated plastic foil (metal-side outwards) and braid of tinned copper wires, braid coverage min. 70 % (nominal value)
Outer sheath	PVC compound colour: black

Electrical properties at 20 °C

Specific volume resistivity	> 20 G Ω x cm
Nominal voltage	EN: 600/1000 V
Rated voltage	UL/CSA: 1000 V
Test voltage	core/core: 4000 V core/screen: 4000 V

Mechanical and thermal properties

Minimum bending radius	occasional flexing: 15 x outer diameter fixed installation: 4 x outer diameter
Temperature range	occasional flexing (EN): -15 °C up to +90 °C max. conductor temperature occasional flexing (UL/CSA): up to +80 °C max. conductor temperature fixed installation (EN): -40 °C up to +90 °C max. conductor temperature fixed installation (UL/CSA): up to +80 °C max. conductor temperature highest permissible short-circuit temperature on the conductor: +250 °C

Creator: SESC/PDC	Document: DB1133600EN	Page 1 of 3
Released: ALTE/PDC	Version: 05	

1133600	DATA SHEET	
valid from: 2026-06-24	ÖLFLEX® SERVO 2XSLCY-JB	

Flammability

flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2
 UL: Vertical flame test VW-1 acc. to UL 1581 § 1080
 CSA: FT1 acc. to CSA C22.2 No. 2556 § 9.3

UV resistance

acc. to EN 50620
 acc. to EN ISO 4892-2, method A (change of colour allowed)
 acc. to EN 50525-1 cable with black sheath are suitable
 for permanent outdoor use

Tests

acc. to IEC 60811, EN 50395, EN 50396, UL 1581, UL 758 and CSA C22.2 No 210

General requirements

These cables are conform to the EU-Directive 2014/35 EU
 (Low Voltage Directive).

A part of these cables (see www.lappkabel.com/cpr) are classified
 in accordance with the EU-Regulation no. 305/2011 (CPR).

Environmental information

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: SESC/PDC	Document: DB1133600EN	Page 2 of 3
Released: ALTE/PDC	Version: 05	

1133600	DATA SHEET	
valid from: 2026-06-24	ÖLFLEX® SERVO 2XSLCY-JB	

Part number	Dimension	Conductor design: max. wire Ø [mm]	Core identification code	Copper braid: max. wire Ø [mm]	Copper braid: nom. cross section [mm²]	Outer Ø (nominal) [mm]	Current ratings at 30°C [A]	Inductance per core at 800 Hz [µH/km]	Capacitance core/core at 800 Hz [nF/km]	Capacitance core/screen at 800 Hz [nF/km]	Transfer impedance at 1 MHz [Ω/km]	Transfer impedance at 10 MHz [Ω/km]	Transfer impedance at 30 MHz [Ω/km]
1133600	4G1.5	0.26	GNYE, BN, BK, GY	0.21	2.5	10.9	23	366	70	110	-	-	240
1133601	4G2.5	0.26	GNYE, BN, BK, GY	0.21	4	12.1	32	340	80	130	18	175	210
1133602	4G4	0.31	GNYE, BN, BK, GY	0.21	4	14.1	42	339	90	150	11	95	210
1133603	4G6	0.31	GNYE, BN, BK, GY	0.21	6	15.6	54	321	90	150	6	50	150
1133604	4G10	0.41	GNYE, BN, BK, GY	0.26	6	18.0	75	301	120	200	7	60	180
1133605	4G16	0.41	GNYE, BN, BK, GY	0.26	6	20.9	100	285	140	230	9	80	190
1133606	4G25	0.41	GNYE, BN, BK, GY	0.26	16	26.0	127	280	140	240	4	32	95
1133607	4G35	0.41	GNYE, BN, BK, GY	0.31	16	29.6	158	271	150	260	3	26	85
1133608	4G50	0.41	GNYE, BN, BK, GY	0.31	16	32.8	192	270	190	320	2	13	40
1133609	4G70	0.41	GNYE, BN, BK, GY	0.31	16	38.0	246	262	190	320	2	18	45
1133610	4G95	0.41	GNYE, BN, BK, GY	0.31	25	42.5	298	261	250	410	2	18	45
1133611	4G120	0.41	GNYE, BN, BK, GY	0.31	25	47.0	346	256	260	430	2	18	45
1133612	4G150	0.41	GNYE, BN, BK, GY	0.41	35	52.9	399	256	270	450	2	18	45
1133613	4G185	0.41	GNYE, BN, BK, GY	0.41	35	57.6	456	255	280	470	2	18	45
1133614	4G240	0.41	GNYE, BN, BK, GY	0.41	35	65.6	538	254	290	480	2	18	45
1133615	3X1.5+3G0.25	0.26	3xGNYE, BN, BK, GY	0.21	2.5	10.9	23	366	70	110	-	-	240
1133616	3X2.5+3G0.5	0.26	3xGNYE, BN, BK, GY	0.21	4	12.0	32	340	80	130	18	175	210
1133617	3X4+3G0.75	0.31	3xGNYE, BN, BK, GY	0.21	6	13.5	42	339	90	150	11	95	210
1133618	3X6+3G1.0	0.31	3xGNYE, BN, BK, GY	0.21	6	14.7	54	321	90	150	6	50	150
1133619	3X10+3G1.5	0.41	3xGNYE, BN, BK, GY	0.26	6	16.7	75	301	120	200	7	60	180
1133620	3X16+3G2.5	0.41	3xGNYE, BN, BK, GY	0.26	10	20.2	100	285	140	230	9	80	190
1133621	3X25+3G4	0.41	3xGNYE, BN, BK, GY	0.26	10	23.4	127	280	140	240	4	32	95
1133622	3X35+3G6	0.41	3xGNYE, BN, BK, GY	0.31	16	26.7	158	271	150	260	3	26	85
1133623	3X50+3G10	0.41	3xGNYE, BN, BK, GY	0.31	16	30.9	192	270	190	320	2	13	40
1133624	3X70+3G10	0.41	3xGNYE, BN, BK, GY	0.31	16	34.4	246	262	190	320	2	18	45
1133625	3X95+3G16	0.41	3xGNYE, BN, BK, GY	0.31	16	38.3	298	261	250	410	2	18	45
1133626	3X120+3G16	0.41	3xGNYE, BN, BK, GY	0.31	25	42.3	346	256	260	430	2	18	45
1133627	3X150+3G25	0.41	3xGNYE, BN, BK, GY	0.41	25	47.5	399	256	270	450	2	18	45
1133628	3X185+3G35	0.41	3xGNYE, BN, BK, GY	0.41	35	51.9	456	255	280	470	2	18	45
1133629	3X240+3G50	0.41	3xGNYE, BN, BK, GY	0.41	35	59.0	538	254	290	480	2	18	45

Creator: SESC/PDC	Document: DB1133600EN	Page 3 of 3
Released: ALTE/PDC	Version: 05	