

17VBS-2606: Straight adapter VBS manifold 26x1"



Commercial information

Aansluitstuk voor de Henco VBS verdeler. Kan enkel gebruikt worden bij de VBS05 of VBS06. Deze fitting is gemaakt uit messing met een RVS huls.

Basic unit dimensions

Height	53 mm
Length	38 mm
Width	38 mm
Net weight	0.125 kg

Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, EMI

Applications

Potable water, Heating, Compressed air, Cooling, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Outer pipe diameter connection 1	20 Millimetre
Surface protection connection 1	Untreated	Length	38 Millimetre
Surface treatment connection 1	Untreated	Length of connection 1	37 Millimetre
Material connection 2	Brass	Working length connection 1	37 Millimetre
Material quality connection 2	CuZn40Pb2 (CW617N)	Length of connection 2	18 Millimetre
Surface protection connection 2	Untreated	Working length connection 2	18 Millimetre
Surface treatment connection 2	Untreated	Wrench width	0 Millimetre
Shape	Straight	Wrench width union nut	0 Millimetre
Reducing	✗	Medium temperature (continuous)	-10 70 Degrees celsius
Eccentric	✗	Max. operating pressure at 20 °C	16 Bar
System specific	✓	Standard Dimension Ratio (SDR)	0
Connection 1	Press sleeve		
Connection 2	External thread conical BSPT-R (ISO 7-1 / EN 10226-1)		
Main colour fitting	Brass		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With connection indicator	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		