Technical data sheet

CML3518 profile rail, slot 17 mm, FS, perforated

Item number: 1104310

Light-duty profile rail, perforated, slot width 17 mm.



CE 17 H E30 E60 E90

St	Steel
FS	Strip galvanised

Master data

Item number	1104310
Type	CML3518P0600FS
Description 1	Profile rail
Description 2	perforated, slot 17mm
Manufacturer	OBO
Dimension	600x35x18
Material	Steel
Surface	Strip galvanised
Surface standard	DIN EN 10346
Smallest sales unit	10
Unit of quantity	Piece
Weight	42.6 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	1,0688 kg CO2e / 1 Piece

Technical data sheet

CML3518 profile rail, slot 17 mm, FS, perforated

Item number: 1104310

Dimensions



Length	600 mm
Width	35 mm
Height	18 mm
Dimension L	600 mm

Technical data

Breakable	no
Type of perforation	Perforated back
Version for	Single profile
Drill hole spacing, centre	25 mm
Maintain electrical functions	yes
Material thickness	1.25 mm
With perforation	yes
With toothing	no
Profile shape	C profile
ROHS-conformant	yes
Rustproof steel, pickled	no
Slot width	17 mm
Static value A	0.88 cm²
Static value Iy	0.41 cm⁴
Static value Iz	1.81 cm⁴
Static value Wy	0.41 cm³
Static value Wz	1.03 cm³