

## Expospot 90 cardan round

EXPOSPOT 90 CARDAN VHO RA90 3000K MB WHITE

2070123



### Product features

- Integrated LED cardanic accent downlight, single head, ideal for retail and display applications, die-cast aluminium body, white colour housing, passive cooling, beam angle: 44°, optics: aluminium reflector and lens combination, colour temperature: 3000K, total system power: 56W, total fixture output: 5330lm, 95lm/W, LOR: 100%, colour rendering: Ra 90 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, electronic driver, non-dimmable, electrical protection: CLASS II, ingress protection rating: IP20, suitable for internal environment only, ceiling cut-out: 148mm, outer dimensions: 163x104mm, weight: 0.77kg.




### PRODUCT OVERVIEW

Product name	EXPOSPOT 90 CARDAN VHO RA90 3000K MB WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
General application	Hospitality, Museums & Galleries, Retail
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	5330
Luminaire efficacy (lm/W)	95
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	44
Photobiological Risk Group	RG1
Total power consumption (W)	56
Electrical protection	Class II
Control gear type	Electronic ballast
Control gear mounting	Remote
Dimmable	No
Dimming method	N/A
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5025768701230

### PHOTOMETRY

## Expospot 90 cardan round EXPOSPOT 90 CARDAN VHO RA90 3000K MB WHITE 2070123



Distance [m]	Cone diameter [m]	E(0°) [lx]	E(C/2) [lx]	U(0°) [lx]	U(C/2) [lx]
0.5	0.41	2420	221*	2420	990
1.0	0.81	605	221*	605	249
1.5	1.22	278	221*	278	100
2.0	1.62	155	221*	155	59
2.5	2.03	99	221*	99	38
3.0	2.44	66	221*	66	26

Distance [m] Cone diameter [m]  
C0-C180 (Half beam angle: 44.2°)

### TECHNICAL DRAWINGS

