

# Specifications

Photo is representative

## Eaton 064978

Eaton Moeller® series P1 Main switch, P1, 32 A, rear mounting, 3 pole + N, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position

### General specifications

|                             |   |
|-----------------------------|---|
| <b>PRODUCT NAME</b>         | Eaton Moeller® series P1 Main switch  |
| <b>CATALOG NUMBER</b>       | 064978  |
| <b>MODEL CODE</b>           | P1-32/V/SVB-SW/N/H11  |
| <b>EAN</b>                  | 4015080649786   |
| <b>PRODUCT LENGTH/DEPTH</b> | 90 mm   |
| <b>PRODUCT HEIGHT</b>       | 70 mm   |
| <b>PRODUCT WIDTH</b>        | 78 mm   |
| <b>PRODUCT WEIGHT</b>       | 0.287 kg  |
| <b>WARRANTY</b>             | Not Applicable  |
| <b>CERTIFICATIONS</b>       | IEC/EN 60947<br>IEC/EN 60947-3<br>VDE 0660<br>UL<br>UL 60947-4-1<br>CSA File No.: 012528<br>IEC/EN 60204<br>CSA Class No.: 3211-05<br>CSA-C22.2 No. 60947-4-1-14<br>UL Category Control No.: NLRV<br>UL File No.: E36332<br>CE<br>CSA<br>CSA-C22.2 No. 94 |
| <b>CATALOG NOTES</b>        | Rated Short-time Withstand Current (I <sub>cw</sub> ) for a time of 1 second  |
| <b>GLOBAL CATALOG</b>       | 064978  |

## Product specifications

|   |  |
|---|--|
| <b>PRODUCT CATEGORY</b>   | Main switch  |
| <b>FEATURES</b>   | Version as maintenance-<br>/service switch<br>Version as main switch   |
| <b>ACTUATOR COLOR</b>   | Black  |
| <b>10.10 TEMPERATURE RISE</b>   | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>   | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>10.2.2 CORROSION RESISTANCE</b>  | Meets the product standard's requirements.   |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.   |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.   |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.   |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | UV resistance only in connection with protective shield.   |
| <b>10.2.5 LIFTING</b>   | Does not apply, since the entire switchgear needs to be evaluated.   |
| <b>10.2.6 MECHANICAL IMPACT</b>   | Does not apply, since the entire switchgear needs to be evaluated.   |

|   |  |
|---|--|
| <b>10.2.7 INSCRIPTIONS</b>                                      | Meets the product standard's requirements.                                     |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                  | Does not apply, since the entire switchgear needs to be evaluated.             |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                   | Meets the product standard's requirements.                                     |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                   | Does not apply, since the entire switchgear needs to be evaluated.             |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>   | Does not apply, since the entire switchgear needs to be evaluated.             |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>        | Is the panel builder's responsibility.   |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                 | Is the panel builder's responsibility.   |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                 | Is the panel builder's responsibility.   |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                         | Is the panel builder's responsibility.   |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b> | Is the panel builder's responsibility.   |
| <b>FITTED WITH:</b>   | Black rotary handle and locking ring   |
| <b>OPERATING FREQUENCY</b>                                      | 1200 Operations/h  |
| <b>POLLUTION DEGREE</b>   | 3  |
| <b>CLIMATIC PROOFING</b>  | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>                   | 6000 V AC  |
| <b>RATED PERMANENT CURRENT AT AC-21, 400 V</b>                  | 32 A   |
| <b>RATED PERMANENT CURRENT AT AC-23, 400 V</b>                  | 32 A   |
| <b>RATED UNINTERRUPTED CURRENT (IU)</b>                         | 32 A   |
| <b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>       | 0 W  |
| <b>SWITCHING POWER AT 400 V</b>                                 | 15 kW  |

|  |  |
|--|--|
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 500 V, 50<br/>HZ</b>       | 18.5 kW                                      |
| <b>DEVICE CONSTRUCTION</b>   | Built-in device fixed built-<br>in technique |
| <b>RATED SHORT-TIME<br/>WITHSTAND CURRENT<br/>(ICW)</b>            | 0.64 kA<br>640 A, Contacts, 1 second         |
| <b>ELECTRICAL<br/>CONNECTION TYPE OF<br/>MAIN CIRCUIT</b>          | Screw connection                             |
| <b>MOUNTING POSITION</b>   | As required                                  |
| <b>ACTUATOR TYPE</b>   | Door coupling rotary drive                   |
| <b>AMBIENT OPERATING<br/>TEMPERATURE - MAX</b>                     | 50 °C  |
| <b>AMBIENT OPERATING<br/>TEMPERATURE - MIN</b>                     | -25 °C                                       |
| <b>AMBIENT OPERATING<br/>TEMPERATURE<br/>(ENCLOSED) - MAX</b>      | 40 °C  |
| <b>AMBIENT OPERATING<br/>TEMPERATURE<br/>(ENCLOSED) - MIN</b>      | -25 °C                                       |
| <b>ASSIGNED MOTOR<br/>POWER AT 115/120 V, 60<br/>HZ, 1-PHASE</b>   | 1 HP   |
| <b>ASSIGNED MOTOR<br/>POWER AT 200/208 V, 60<br/>HZ, 1-PHASE</b>   | 2 HP   |
| <b>ASSIGNED MOTOR<br/>POWER AT 200/208 V, 60<br/>HZ, 3-PHASE</b>   | 3 HP   |
| <b>ASSIGNED MOTOR<br/>POWER AT 230/240 V, 60<br/>HZ, 1-PHASE</b>   | 3 HP   |
| <b>ASSIGNED MOTOR<br/>POWER AT 230/240 V, 60<br/>HZ, 3-PHASE</b>   | 7.5 HP                                       |
| <b>ASSIGNED MOTOR<br/>POWER AT 460/480 V, 60<br/>HZ, 3-PHASE</b>   | 10 HP  |
| <b>ASSIGNED MOTOR<br/>POWER AT 575/600 V, 60<br/>HZ, 3-PHASE</b>   | 15 HP  |
| <b>EQUIPMENT HEAT<br/>DISSIPATION, CURRENT-<br/>DEPENDENT PVID</b> | 0 W  |
| <b>HEAT DISSIPATION<br/>CAPACITY PDISS</b>                         | 0 W  |

|  |   |
|--|---|
| <b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>       | 1.8 W   |
| <b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>     | 0   |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b> | 1   |
| <b>RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)</b>            | 80 kA   |
| <b>OVERVOLTAGE CATEGORY</b>                                    | III   |
| <b>CONTROL CIRCUIT RELIABILITY</b>                             | 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)   |
| <b>DEGREE OF PROTECTION (FRONT SIDE)</b>                       | IP65  |
| <b>NUMBER OF POLES</b>   | 4   |
| <b>MOUNTING METHOD</b>   | Rear mounting   |
| <b>DEGREE OF PROTECTION</b>                                    | NEMA 12   |
| <b>SUITABLE FOR</b>  | Branch circuits, suitable as motor disconnect, (UL/CSA)   |
| <b>LOCKING FACILITY</b>  | Lockable in the 0 (Off) position  |
| <b>FUNCTIONS</b>   | STOP function<br>Interlockable  |
| <b>NUMBER OF SWITCHES</b>                                      | 1   |
| <b>SAFE ISOLATION</b>  | 440 V AC, Between the contacts, According to EN 61140   |
| <b>SCREW SIZE</b>  | M4, Terminal screw  |
| <b>SHOCK RESISTANCE</b>  | 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms   |
| <b>LIFESPAN, MECHANICAL</b>                                    | 300,000 Operations  |
| <b>LOAD RATING</b>   | 2 x I <sub>e</sub> (with intermittent operation class 12, 25 % duty factor)<br>1.3 x I <sub>e</sub> (with intermittent operation class 12, 60 % duty factor)<br>1.6 x I <sub>e</sub> (with intermittent operation class 12, 40 % duty factor) |

|  |   |
|--|---|
| <b>SWITCHING CAPACITY<br/>(AUXILIARY CONTACTS,<br/>GENERAL USE)</b>              | 10A, IU, (UL/CSA)   |
| <b>SWITCHING CAPACITY<br/>(AUXILIARY CONTACTS,<br/>PILOT DUTY)</b>               | A600 (UL/CSA)<br>P600 (UL/CSA)  |
| <b>TERMINAL CAPACITY</b>   | 2 x (1.5 - 6) mm <sup>2</sup> , solid or<br>stranded<br>14 - 8 AWG, solid or<br>flexible with ferrule<br>1 x (1 - 4) mm <sup>2</sup> , flexible<br>with ferrules to DIN 46228<br>2 x (1 - 4) mm <sup>2</sup> , flexible<br>with ferrules to DIN 46228<br>1 x (1.5 - 6) mm <sup>2</sup> , solid or<br>stranded |
| <b>SWITCHING CAPACITY<br/>(MAIN CONTACTS,<br/>GENERAL USE)</b>                   | 30 A, Rated uninterrupted<br>current max. (UL/CSA)  |
| <b>SAFETY PARAMETER (EN<br/>ISO 13849-1)</b>                                     | B10d values as per EN ISO<br>13849-1, table C.1   |
| <b>NUMBER OF AUXILIARY<br/>CONTACTS (NORMALLY<br/>OPEN CONTACTS)</b>             | 1   |
| <b>NUMBER OF CONTACTS<br/>IN SERIES AT DC-23A, 120<br/>V</b>                     | 3   |
| <b>NUMBER OF CONTACTS<br/>IN SERIES AT DC-23A, 24 V</b>                          | 1   |
| <b>NUMBER OF CONTACTS<br/>IN SERIES AT DC-23A, 48 V</b>                          | 2   |
| <b>NUMBER OF CONTACTS<br/>IN SERIES AT DC-23A, 60 V</b>                          | 2   |
| <b>RATED BREAKING<br/>CAPACITY AT 220/230 V<br/>(COS PHI TO IEC 60947-3)</b>     | 260 A   |
| <b>RATED BREAKING<br/>CAPACITY AT 400/415 V<br/>(COS PHI TO IEC 60947-3)</b>     | 300 A   |
| <b>RATED BREAKING<br/>CAPACITY AT 500 V (COS<br/>PHI TO IEC 60947-3)</b>         | 290 A   |
| <b>RATED BREAKING<br/>CAPACITY AT 660/690 V<br/>(COS PHI TO IEC 60947-3)</b>     | 250 A   |
| <b>RATED MAKING<br/>CAPACITY UP TO 690 V<br/>(COS PHI TO IEC/EN<br/>60947-3)</b> | 320 A   |
| <b>RATED OPERATING</b>   | 690 V   |

|   |   |
|---|---|
| <b>VOLTAGE (UE) - MAX</b>   |   |
| <b>RATED OPERATING VOLTAGE (UE) - MIN</b>                                     | 690 V   |
| <b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>                             | 690 V   |
| <b>SHORT-CIRCUIT CURRENT RATING (BASIC RATING)</b>                            | 5 kA, SCCR (UL/CSA)<br>110A, max. Fuse, SCCR (UL/CSA)           |
| <b>SHORT-CIRCUIT CURRENT RATING (HIGH FAULT)</b>                              | 50 A, Class J, max. Fuse, SCCR (UL/CSA)<br>10 kA, SCCR (UL/CSA) |
| <b>SHORT-CIRCUIT PROTECTION RATING</b>  | 50 A gG/gL, Fuse, Contacts                                      |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-21, 440 V</b>                         | 32 A  |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-23A, 230 V</b>                        | 32 A  |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-23A, 400 V, 415 V</b>                 | 32 A  |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-23A, 500 V</b>                        | 30 A  |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-23A, 690 V</b>                        | 19.8 A  |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V</b>            | 26.4 A  |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V</b>            | 26.4 A  |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V</b>                          | 23.4 A  |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V</b>                   | 14.7 A  |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-1, LOAD-BREAK SWITCHES L/R = 1 MS</b> | 32 A  |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-23A, 120 V</b>                        | 12 A  |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-23A,</b>                              | 25 A  |

|  |         |
|--|---------|
| <b>24 V</b>  |         |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-23A, 48 V</b>                | 25 A    |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-23A, 60 V</b>                | 25 A    |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 32 A    |
| <b>RATED OPERATIONAL POWER AT AC-23A, 220/230 V, 50 HZ</b>           | 7.5 kW  |
| <b>RATED OPERATIONAL POWER AT AC-23A, 400 V, 50 HZ</b>               | 15 kW   |
| <b>RATED OPERATIONAL POWER AT AC-23A, 500 V, 50 HZ</b>               | 18.5 kW |
| <b>RATED OPERATIONAL POWER AT AC-23A, 690 V, 50 HZ</b>               | 15 kW   |
| <b>RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ</b>             | 13 kW   |
| <b>RATED OPERATIONAL POWER AT AC-3, 415 V, 50 HZ</b>                 | 13 kW   |
| <b>RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ</b>                 | 15 kW   |
| <b>HOUSING COLOR</b>   | Black   |
| <b>HOUSING MATERIAL</b>  | Plastic |

## Resources

|                                   |   |
|-----------------------------------|---|
| <b>BROCHURES</b>                  | <a href="#">Brochure - T Rotary Cam switch and P Switch-disconnector</a>  |
| <b>CATALOGS</b>                   | <a href="#">P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN</a>   |
| <b>DECLARATIONS OF CONFORMITY</b> | <a href="#">eaton-main-switch-declaration-of-conformity-eu250806en.pdf</a>  |
| <b>DRAWINGS</b>                   | <a href="#">eaton-rotary-switches-padlock-t0-main-switch-dimensions.eps</a><br><a href="#">eaton-rotary-switches-mounting-p1-main-switch-dimensions-002.eps</a> |



|                               |   |
|-------------------------------|---|
|                               | <a href="#">eaton-rotary-switches-mounting-p1-main-switch-3d-drawing-002.eps</a><br><br><a href="#">eaton-rotary-switches-t0-main-switch-symbol.eps</a><br><br><a href="#">eaton-general-mounting-p1-main-switch-symbol-002.eps</a> |
| ECAD MODEL                    | <a href="#">ETN.064978.edz</a>  |
| INSTALLATION INSTRUCTIONS     | <a href="#">eaton-switch-disconnector-p1-rear-mounting-il03802004z.pdf</a>  |
| INSTALLATION VIDEOS           | <a href="#">Eaton's P Switch-disconnectors used in a factory</a>  |
| MCAD MODEL                    | <a href="#">eaton-p1_v_svb_n_hi11-3d-model.stp</a><br><br><a href="#">eaton-p1_v_svb_n_hi11-drawing.dwg</a>   |
| PRODUCT NOTIFICATIONS         | <a href="#">MZ008005ZU_Orderform_Customized_Switch.pdf</a><br><br><a href="#">MZ008006ZU_Orderform_Customized_Switch.pdf</a>  |
| SPECIFICATIONS AND DATASHEETS | <a href="#">Eaton Specification Sheet - 064978</a>  |
| WIRING DIAGRAMS               | <a href="#">eaton-rotary-switches-main-switch-p1-main-switch-wiring-diagram.eps</a>   |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc**  
 Eaton House  
 30 Pembroke Road  
 Dublin 4, Ireland  
 Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

