

Myriad V IP65 White Bezel

MYRIAD IP65 4000K PHASE DIM WHITE EM
2049530



Product features

- MYRIAD IP65 4000K PHASE DIM WHITE EM




PRODUCT OVERVIEW

Product name	MYRIAD IP65 4000K PHASE DIM WHITE EM
Technology	LED
Cap/Base	N/A
Mount	Ceiling recessed mounting
Environment	Interior
General application	Hospitality, Office, Retail
ETIM Class	EC001744
Warranty	5 years
Useful luminous flux (Fuse)	1050
Fixture luminous flux (lm)	1050
Luminaire efficacy (lm/W)	88
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	30
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	347
Total power consumption (W)	16
Electrical protection	Class II
Control gear type	LED driver constant current
Control gear mounting	Integral
Dimming method	Mains: leading / trailing edge
IP rating	IP65/20
IK rating	IK02
Product EAN number	5025768495306


PHOTOMETRY

Myriad V IP65 White Bezel MYRIAD IP65 4000K PHASE DIM WHITE EM 2049530



Distance [m]	Cone diameter [m]	50° E(C0)	19.6° E(C90)	Illuminance [lx]
0.5	0.36	8320	2640	
1.0	0.71	1070	340	
1.5	1.07	450	140	
2.0	1.42	320	100	
2.5	1.78	250	80	
3.0	2.14	190	60	

Distance [m] Cone diameter [m]
C0 - C180 (Half beam angle: 39.2°)



Distance [m]	Cone diameter [m]	50° E(C0)	19.6° E(C90)	Illuminance [lx]
0.5	0.36	2080	660	
1.0	0.71	510	160	
1.5	1.07	330	100	
2.0	1.42	240	70	
2.5	1.78	190	55	
3.0	2.14	150	45	

Distance [m] Cone diameter [m]
C0 - C180 (Half beam angle: 39.2°)

TECHNICAL DRAWINGS

