





Replaces K74521/02

Page 1 of 3



Electronic tapware

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Hansgrohe SE

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline

BRL K14018 "Sanitary tapware - Electronic tapware" dated 01-02-2012

which covers the requirements of

EN 15091:2013 "Sanitary tapware – Electronic opening and closing sanitary tapware"

Ron Scheepers

Niwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273

2280 AB RIJSWIJK

The Netherlands

Tel. +31 88 998 44 00

Fax +31 88 998 44 20

info@kiwa.nl

Postbus 70

www.kiwa.nl

Company

Hansgrohe SE

Auestrasse 5-9

77761 SCHILTACH

Germany

Tel. (+49) 783651-1280

Fax (+49) 7836 51-1300

info@hansgrohe.com

www.hansgrohe.com

Certification process consists of initial and regular assessment of:

- quality system
- product

page 2 of 3

Sanitary tapware; Electronic tapware

Technical specification

The products mentioned below belong to this certificate;

AXOR

series CITTERIO	
16 180 180	basic set, built in, combined with:
39 117 xxx	basin mixer with short spout - finish set
39 118 xxx	basin mixer with long spout - finish set
series Uno ²	
16 180 180	basic set, built in, combined with:
38 119 xxx	basin mixer with short spout - finish set
38 120 xxx	basin mixer with long spout - finish set
series Vernis Blend	
71 501 000	basin mixer 230V
71 502 000	basin mixer battery powered
71 503 000	basin tap battery powered
71 504 000	basin tap 230V

page 3 of 3

Sanitary tapware; Electronic tapware

REMARK

The specified products were not yet assessed for compliance with all hygienic aspects as inserted in the "Drinkwaterbesluit" (Drinking Water Decree) and outlined in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" (Materials and chemicals in the supply of drinking water and warm tap water Regulation) dated 01-07-2017, as specified in clause 4.2 of the Kiwa guideline BRL-K14018/02.

Application and use

The electronic taps are designed for application within following limits of use:

- working pressure from 50 kPa up to 1000 kPa;
- water temperature of maximum 90°C.

The recommended limits for correct operation are:

- working pressure of 100 kPa up to 500 kPa;
- water temperature of maximum 65°C.

Marking

The Kiwa®-mark products are marked with the wordmark "KIWA".

Place of the mark:

• on the body.

Compulsory specifications:

- name or mark of the manufacturer; on the body;
- indication of the acoustic group, if classified; on the body;
- indication of the flow rate class; on the body.

Method of marking:

- · non-erasable;
- · visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

· Hansgrohe SE, Schiltach

and, if necessary,

• Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.