

Splashproof single surface-mounting box with one M20 input with cable gland at the top and bottom for one function, black

761-84161



This surface-mounting box with one M20 input with cable gland at the top and bottom is suitable for one function. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in ammonia-rich environments. Colour: black

Technical data

Splashproof single surface-mounting box with one M20 input with cable gland at the top and bottom for one function, black.

- Function: the fixation points are situated 50mm apart on a vertical axis. This size indication is indelibly imprinted on the bottom of each box. The oval screw openings allow for imprecise drilling. By forming a pressure lock, a gasket ensures the protection degree and the double insulation. The box contains two diagonal, knock-out condensation openings
- Number of spaces for mechanisms: Simple faceplate for one switch.
- Material surface-mounting box: the surface-mounting box is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (PP) (UL94-V2/1.6 mm)
- Colour: black
- Colour RAL (approximately): 9005
- Surface treatment: coloured in mass
- Protection degree: see protection degree of the mounted function
- Impact resistance: the combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Marking: CE

