

## Insaver HO Topper LED II 225

*Insaver HO Topper LED II 225 RO 25W NW*  
3033949



### Product features

- IP44 from the front round LED downlight with polycarbonate diffuser with a white bezel. Polycarbonate diffuser with a white bezel. Shallow recess depth (<65mm). Available in 12, 15, 21 & 25W in 150mm, 175mm, 205mm & 225mm cut out sizes. Perfect for up to 2x26W CFL replacement. Includes loop-in loop-out facility for quick installation.



### PRODUCT OVERVIEW


Product name	Insaver HO Topper LED II 225 RO 25W NW
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Interior
General application	Hospitality
ETIM Class	EC001744
E-number SE	7465634
Warranty	5 years
Useful luminous flux (Fuse)	2400
Fixture luminous flux (lm)	2400
Luminaire efficacy (lm/W)	104
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	74
Glare control	< 24
Photobiological Risk Group	RG0
Total power consumption (W)	25
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9010 - Pure white
IP rating	IP44/20
IK rating	IK07
Product EAN number	8711971339496

## Insaver HO Topper LED II 225 *Insaver HO Topper LED II 225 RO 25W NW* 3033949

### PHOTOMETRY

0.5	0.76 0.77	E(0°) 5402 E(C90) 27.2° 1389 E(C270) 27.2° 1389
1.0	1.60 1.63	E(0°) 1380 E(C90) 27.2° 342 E(C270) 27.2° 342
1.5	2.28 2.30	E(0°) 800 E(C90) 27.2° 400 E(C270) 27.2° 400
2.0	3.04 3.07	E(0°) 580 E(C90) 27.2° 290 E(C270) 27.2° 290
2.5	3.60 3.64	E(0°) 476 E(C90) 27.2° 238 E(C270) 27.2° 238
3.0	4.55 4.60	E(0°) 380 E(C90) 27.2° 190 E(C270) 27.2° 190

Distance [m] Core diameter [m] Illuminance [lx]  
 — C0 - C180 (Half beam angle: 75.0°)  
 — C90 - C270 (Half beam angle: 74.4°)



### TECHNICAL DRAWINGS

