

18EK05-03: Straight adapter manifold 3/8"



Commercial information

Adapter - 3/8" female for appendages with eurocone connector

- Extra adapter for the Henco PVDF manifold offers the possibility to equip the installation with an air vent
- Made from high-quality, lead-free brass alloy CW724
- Corrosion-resistant, stress corrosion-free

Basic unit dimensions

Height	32 mm
Length	32 mm
Width	32 mm
Net weight	0.049 kg

Certificates

QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, WRAS, KOMO, STF, GOST-R, TSU, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material	Kunststof/messing	Bend radius	0 Millimetre
Material connection 1	Polyvinylidene fluoride (PVDF)	Length	31.5 Millimetre
Material quality	Polyvinylidene fluoride (PVDF)	Medium temperature (continuous)	-10 70 Degrees celsius
Surface protection connection 1	Untreated	Max. operating pressure at 20 °C	16 Bar
Surface treatment connection 1	Untreated	Standard Dimension Ratio (SDR)	0
Material connection 2	Brass		
Surface protection connection 2	Untreated		
Surface treatment connection 2	Untreated		
Shape	Straight		
Reducing	✘		
Eccentric	✘		
System specific	✓		
Connection 1	Euroconus (expired)		
Nominal diameter connection 2	3/4 inch (20)		
Connection 2	Internal thread cylindrical BSPT-Rp (ISO 7-1 / EN 10226-1)		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✘		
High tensile strength	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✘		
Capped	✘		
With connection indicator	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✘		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		