

RANA NEO Surface 1500
RANA NEO 9500LM S 1500 840 CC 2L WHITE
0054259



Product features

- Surface or Suspended LED luminaire with Micro Prismatic Optic, Direct Light Distribution, Luminaire Dimensions: 1447x187x56mm, White body colour, IP20, IK07, Constant Current, Low LED flicker (+/- 5%), Neutral White (4000K) LED Colour Temperature, 9500lm, 70W, 135lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<17, Luminance at 65° < 3000 cd/m2, Lifespan: 96,000 hours L80B20, Quick electrical connection with push-connectors in the luminaire, Glow Wire Test 850°C.




PRODUCT OVERVIEW

Product name	RANA NEO 9500LM S 1500 840 CC 2L WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
General application	Education, Office
ETIM Class	EC002892
Warranty	5 years
Useful luminous flux (Fuse)	9500
Fixture luminous flux (lm)	9500
Luminous flux (lm)	9500
Luminaire efficacy (lm/W)	136
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 17
Photobiological Risk Group	RG0
Total power consumption (W)	74
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288542591

PHOTOMETRY

RANA NEO Surface 1500
RANA NEO 9500LM S 1500 840 CC 2L WHITE
0054259



TECHNICAL DRAWINGS

