


## VS-0604: Manifold Reducer with O-ring 1"x1/2"



### Commercial information

Brass reducer with O-ring for distributor

#### Basic unit dimensions

Height	41 mm
Length	16 mm
Width	41 mm
Net weight	0.079 kg

#### Certificates

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material connection 2	Brass	Length	15.5 Millimetre
Reducing	✘	Wrench width union nut	0 Millimetre
Eccentric	✘	Medium temperature (continuous)	-10 70 Degrees celsius
System specific	✓	Max. operating pressure at 20 °C	10 Bar
Nominal diameter connection 2	1 inch (25)	Standard Dimension Ratio (SDR)	0
Main colour fitting	Brass		
With buffer stud	✘		
High tensile strength	✘		
With thermal insulation	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✘		
With connection indicator	✘		
With drain valve	✘		
With de-aerator	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✘		
KIWA certified	✘		
Gastec QA mark	✘		
KOMO certified	✘		
Type approval according to BBR/EKS	✘		