

N06: Nipple for Henco Press 26P-Z 1" x 1"



Commercial information

Nippel voor referentie 26P-Z, aansluiting met wartel, vlakke dichting

Basic unit dimensions

Height	13 mm
Length	31 mm
Width	13 mm
Net weight	0.055 kg

Certificates

Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Material quality connection 1	CuZn40Pb2 (CW617N)	Length	31 Millimetre
Surface protection connection 1	Untreated	Wrench width	0 Millimetre
Surface treatment connection 1	Untreated	Wrench width union nut	0 Millimetre
Material connection 2	Brass	Medium temperature (continuous)	-10 70 Degrees celsius
Material quality connection 2	CuZn40Pb2 (CW617N)	Max. operating pressure at 20 °C	10 Bar
Surface protection connection 2	Untreated	Standard Dimension Ratio (SDR)	0
Surface treatment connection 2	Untreated		
Shape	Straight		
Reducing	✓		
Eccentric	✗		
System specific	✓		
Connection 1	External thread cylindrical BSPP-G (ISO 228-1)		
Connection 2	External thread cylindrical BSPP-G (ISO 228-1)		
Main colour fitting	Brass		
Material sealing	Brass		
With buffer stud	✓		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✗		
KIWA certified	✗		
Gastec QA mark	✗		
KOMO certified	✗		
Type approval according to BBR/EKS	✗		