

Product data sheet

Item No. 91.922.3053.1

Male connector with strain relief GST15I2S S1 ZR1W SW

Connector GST15i2, 2 pole, male, screw connection, 250V/16A, color of coding: black, color of housing: black



Item No.	91.922.3053.1
EAN	4015573916111
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Connection Data

Cable diameter	7.7 mm
Cable diameter 2	6 mm
Connection cross section solid	1.5 mm ²
Cross section solid 2	0.5 mm ²
Connection cross section stranded	1.5 mm ²
Cross section stranded 2	0.5 mm ²

Terminations per pole	1
-----------------------	---

Model

Model	male
Number of poles	2
Connection type	Screw connection
Degree of protection (IP)	IP40

Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	53.2 mm
Width	17.7 mm
Height	13.8 mm

Technical drawing

