

INSTALLATION SYSTEMS RECESSED INTO THE FLOOR



Offices



Meeting rooms


Educational
centres


Libraries


Conference
centres


Museums

THE PERFECT SOLUTION FOR SHALLOW FLOORS

1 / Trim

For a perfect finish (optional)

2 / Cover

The cover has a thickness of 6 mm to customize the hinged cover with the floor finish (carpet, parquet or other finishes). With 3 opening positions (box with 3 double modules) and 2 separate rubber grommets.

3 / Versatile pre-punched holes

The mechanism-holders have punched holes for 10 mm and 20 mm tubes and two spaces for threading voice and data cabling.

4 / Mechanism-holders

Plug&Play mechanism-holders modules that allow quick and easy installation.

5 / Shallow

Perfect solution for shallow floors.

6 / Concrete floor tray


Required element for concrete floor installation. It is not required for raised floor installation.

SHALLOW

The perfect solution for shallow floors, raised or pavement.

INTEGRATES INTO ANY SPACE

The angle of the mechanisms allows the cover to be closed with the box connected, concealing the connections




COMPATIBLE WITH HIGHER CATEGORIES

Thanks to the angle of the mechanisms and the pre-punched inlet holes, there are no bends in the Voice, Data and multimedia cabling.



ADJUSTABLE TO CHANGES IN OFFICE FURNITURE

Thanks to the two separate cable outlets and the different opening positions of the cover, it can be adapted to changes in furniture location.



SHALLOW FLOOR BOXES

SQUARE FLOOR BOXES

	ART. NO.	DESCRIPTION	
	KF200 /1	K45 4 wide mechanisms and 2 narrow mechanisms	
+TRIM COVER		52053202-035	

ROUND FLOOR BOXES

	ART. NO.	DESCRIPTION	
	KF300C /1	K45 6 wide mechanisms and 3 narrow mechanisms	
+TRIM COVER		52053203-035	

SQUARE FLOOR BOXES

	ART. NO.	DESCRIPTION	
	KF400 /1	K45 8 wide mechanisms and 4 narrow mechanisms	
+TRIM COVER		52053204-035	

CONCRETE FLOOR TRAYS

	ART. NO.	DESCRIPTION		ART. NO.	DESCRIPTION		ART. NO.	DESCRIPTION
	G201	For reference KF200 /1		G301C	For reference KF300C /1		G401	For reference KF400 /1

<



K45 technical Information

Plastic parts manufactured using halogen-free, self-extinguishing thermoplastic materials, guaranteeing no flame spread in case of fire and low toxicity in the event of smoke generation.




HALOGEN-FREE,
SELF-EXTINGUISHING
THERMOPLASTIC MATERIALS

SHALLOW FLOOR BOXES


- Product designed according to the Safety Requirements of Directive 2006/95/EC (Low Voltage) through compliance with UNE-EN-60670 standard.
- Product with CE marking **CE**.
- IP protection degree: 4X
- IK impact resistance degree: 08
- Temperature range during installation: -5 °C to +60 °C
- Maximum temperature during construction work of +90 °C (installed with service box)

FLOOR BOXES


2 double modules




3 double modules



4 double modules



Art. No.	No. of double modules	Dimensions X	No. of pre-punched holes per module	Dimensions Z	Maximum load (kg)
KF200/1	2	64	3 x Ø 10 2 x Ø 20 2 x 22 x 34	11 to 48	400
KF300C/1	3				790
KF400/1	4				770




Dimensions in mm



SHALLOW FLOOR BOXES


INSTALLATION IN RAISED FLOOR

2 double modules




Art. No.	Opening dimensions AxB
KF200/1	250 x 178

3 double modules



Art. No.	Opening dimensions AxB
KF300C/1	300


4 double modules




Art. No.	Opening dimensions AxB
KF400/1	250 x 327

INSTALLATION IN CONCRETE FLOOR


2 double modules



3 double modules




4 double modules



TRAYS FOR CONCRETE FLOOR


ART. NO.
G201

2 double modules



ART. NO.
G301C

3 double modules



ART. NO.
G401

4 double modules

