

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number: 19460204

Reviewed on: 26.03.2025

Page : 1 / 12

01 Identification of the substance/mixture and of the company undertaking

• 1.1 Product identifier

- Trade name:
senotherm® Ofenspray 400ml gußgrau 17-1644-704206
- Article number:
704206

Intended use:
Industrial applications
color spray

- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Not determined.

• 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:
WEILBURGER Coatings GmbH
Ahäuserweg 12-22
D-35781 Weilburg
Telefon: 00496471 315-0
Fax : 00496471 315-116
- Further information obtainable from:
Product safety department. Tel. +49 (0) 6471 315 177 Fax +49 (0) 6471 315 5177 E-Mail: SDS-Info@weilburger.com
- 1.4 Emergency telephone number:
(Carechem 24): Europe:+44 1235 239670 / Germany:+49 89 220 61012 / Middle East/Africa:+44 1235 239671 / Middle East (arabic language):+44 1273 289454 / America:+1 215 207 0061 / Brazil:+55 11 3197 5891 / East Asia/South East Asia (without China):+65 3158 1412

02 Hazards identification

• 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Aerosol 1 - H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2 - H315 Causes skin irritation.
Eye Irrit. 2 - H319 Causes serious eye irritation.
STOT SE 3 - H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.



GHS08

STOT RE 2 - H373 May cause damage to the central nervous system, the

(continued on page 2)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number: 19460204

Reviewed on: 26.03.2025

Page : 2 / 12

PRODUCT : senotherm® Ofenspray 400ml gußgrau 17-1644-704206

(continued of page 1)

kidneys, the liver and the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalative.
Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

• 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms



GHS02



GHS07



GHS08

- Signal word
Danger

- Hazard-determining components of labelling:

acetone / Reaction mass from ethylbenzol and xylene / Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) / 2-methoxy-1-methylethyl acetate

- Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system, the kidneys, the liver and the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalative.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P302+P352 IF ON SKIN: Wash with plenty of water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

• 2.3 Other hazards

- Results of PBT and vPvB assessment

- PBT:

Not applicable.

- vPvB:

Not applicable.

03 Composition/information on ingredients

• 3.2 Chemical characterization: Mixtures

- Description:

Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

CAS Number

67-64-1

acetone

%

25,01- 50,00

(continued on page 3)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number: 19460204

Reviewed on: 26.03.2025

Page : 3 / 12

PRODUCT : senotherm® Ofenspray 400ml gußgrau 17-1644-704206

(continued of page 2)

	EC number: 200-662-2	
	Record number 01-2119471330-49-XXXX	
	Flam. Liq. 2 - H225; Eye Irrit.	
	2 - H319, STOT SE 3 - H336; EUH066	
106-97-8	butane	10,01- 25,00
	EC number: 203-448-7	
	substance with a Community workplace exposure limit.	
	Flam. Gas 1A - H220; Press. Gas	
	(Liq.) - H280	
78-83-1	2-methylpropan-1-ol	0,1- 1,00
	EC number: 201-148-0	
	Record number 01-2119484609-23-XXXX	
	Eye Dam. 1 - H318; Flam. Liq. 3	
	- H226; Skin Irrit. 2 - H315, STOT SE	
	3 - H335-H336	
-	Reaction mass from ethylbenzol and xylene	10,01- 25,00
	EC number: 905-588-0	
	Record number 01-2119486136-34-XXXX	
	STOT RE 2 - H373, Asp. Tox. 1 - H304;	
	Flam. Liq. 3 - H226; Acute Tox.	
	4 - H312, Acute Tox. 4 - H332, Skin Irrit. 2	
	- H315, Eye Irrit. 2 - H319, STOT SE 3 -	
	H335	
*	Dermal: ATE = 1100 mg/kg	
108-65-6	2-methoxy-1-methylethyl acetate	1,01- 02,50
*	EC number: 203-603-9	
*	Record number 01-2119475791-29-XXXX	
*	Flam. Liq. 3 - H226; STOT SE 3 -	
*	H336	
-	Hydrocarbons, C9-C12, n-alkanes, isoalkanes,	2,51- 10,00
*	cyclics, aromatics (2-25%)	
*	EC number: 919-446-0	
*	Record number 01-2119458049-33-XXXX	
*	STOT RE 1 - H372, Asp. Tox. 1 - H304;	
*	Flam. Liq. 3 - H226; STOT SE 3 -	
*	H336; Aquatic Chronic 2 - H411; EUH066	

- Additional information:
For the wording of the listed risk phrases refer to section 16.

GB

(continued on page 4)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number: 19460204

Reviewed on: 26.03.2025

Page : 4 / 12

PRODUCT : senotherm® Ofenspray 400ml gußgrau 17-1644-704206

(continued of page 3)

04 First aid measures

- **General information:**
In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- **After inhalation:**
Remove to fresh air, keep patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.
- **After skin contact:**
Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners.
- **After eye contact:**
Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.
- **After swallowing:**
If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
- **Information for doctor:**
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

05 Firefighting measures

- **Suitable extinguishing agents:**
alcohol resistant foam, CO₂, powder, water spray/mist
- **For safety reasons unsuitable extinguishing agents:**
water jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **Protective equipment:**
Appropriate self-contained breathing apparatus may be required.
- **Additional information**
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.

06 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.
- **6.2 Environmental precautions:**
Do not allow to enter drains or water courses. If the product enters drains or sewers the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the National Rivers Authority.
- **6.3 Methods and material for containment and cleaning up:**
Absorb liquid components with liquid-binding material.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.

GB

(continued on page 5)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number: 19460204

Reviewed on: 26.03.2025

Page : 5 / 12

PRODUCT : senotherm® Ofenspray 400ml gußgrau 17-1644-704206

(continued of page 4)

07 Handling and storage

- **Handling:**

- 7.1 Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits. Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. The product may charge electrostatically. Use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing. Non-sparking tools should be used. Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in areas of storage and use. For protection, see Section 8.

- **Storage:**

- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

- Further information about storage conditions:

Protect from heat and direct sunlight.

Store under lock and key and out of the reach of children.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

- Storage class:

2 B

- **7.3 Specific end use(s)**

No further relevant information available.

08 Exposure controls/personal protection

- **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

WEL

Short-term value	3620	mg/m3
	1500	ppm
Long-term value	1210	mg/m3
	500	ppm

106-97-8 butane

OEL

Short-term value	1810	mg/m3
	750	ppm
Long-term value	1450	mg/m3
	600	ppm

78-83-1 2-methylpropan-1-ol

WEL

Short-term value	231	mg/m3
	75	ppm
Long-term value	154	mg/m3
	50	ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL

Short-term value	548	mg/m3
	100	ppm

(continued on page 6)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number: 19460204

Reviewed on: 26.03.2025

Page : 6 / 12

PRODUCT : senotherm® Ofenspray 400ml gußgrau 17-1644-704206

(continued of page 5)

Long-term value	274	mg/m3
Sk	50	ppm
- ethylbenzene		
WEL		
Short-term value	552	mg/m3
	125	ppm
Long-term value	441	mg/m3
	100	ppm
Sk		
- xylene		
WEL		
Short-term value	441	mg/m3
	100	ppm
Long-term value	220	mg/m3
	50	ppm

Sk; BMGV

• **Additional information:**

The lists that were valid during the creation were used as basis.

• **Personal protective equipment:**

• General protective and hygienic measures:

All parts of the skin should be washed after contact.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Short term filter device:

Filter A/P2

• Protection of hands:

To avoid skin problems reduce the wearing of gloves to the required minimum.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

If only a short-term loading of the glove material by splashes is expected, tricoted gloves with higher wearability for the better acceptance of the users are recommended.

Solvent resistant gloves

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Eye protection designed to protect against liquid splashes should be worn.

• Body protection:

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

GB

(continued on page 7)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number: 19460204

Reviewed on: 26.03.2025

Page : 7 / 12

PRODUCT : senotherm® Ofenspray 400ml gußgrau 17-1644-704206

(continued of page 6)

09 Physical and chemical properties

General Information

Appearance:

Form:	Aerosol
Colour:	Grey
Odour:	Like solvents
Odour threshold:	Not determined.
pH-value:	Not determined.

Change in condition

Initial boiling point and boiling range: -44 °C Not applicable, as aerosol.

Flash point: -97 °C Not applicable, as aerosol.

Flammability (solid, gas): Not applicable.

Ignition temperature: 201 °C

Decomposition temperature: Not determined.

Auto-ignition temperature: Not determined.

Explosive properties: Not determined.

Explosion limits:

Lower: 0,60 Vol %

Upper: 13,00 Vol %

Vapour pressure: at 20 °C 8.000,0000 HPa

Density: Not determined.

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

Solvent content:

Organic solvents: 68,75 %

Solids content: 11,58 %

9.2 Other information

No further relevant information available.

*

10 Stability and reactivity

• **Conditions to be avoided:**

Staple under the recommended storage and handling conditions (see Section 7).

• **10.3 Possibility of hazardous reactions**

No dangerous reactions known.

• **10.4 Conditions to avoid**

No further relevant information available.

• **10.5 Incompatible materials:**

No further relevant information available.

• **10.6 Hazardous decomposition products:**

In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, and oxides of nitrogen may be produced.

GB

(continued on page 8)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number: 19460204

Reviewed on: 26.03.2025

Page : 8 / 12

PRODUCT : senotherm® Ofenspray 400ml gußgrau 17-1644-704206

(continued of page 7)

11 Toxicological information

• **Acute toxicity**

- LD/LC50 values relevant for classification:

67-64-1 acetone

Oral, LD50: 5800 mg/kg (rat)
Dermal, LD50: 20000 mg/kg (Rabbit)

106-97-8 butane

Inhalative, LC50/4h: 658 mg/l (rat)

78-83-1 2-methylpropan-1-ol

Oral, LD50: 3350 mg/kg (rat)
Dermal, LD50: >2830 mg/kg (rat)
Dermal, LD50: 2460 mg/kg (Rabbit)
Inhalative, LC50/4h: 24,6 mg/l (rat)

*

- Reaction mass from ethylbenzol and xylene

Oral, LD50: 8640 mg/kg (rat)
(Xylene)
Oral, LD50: 3500 mg/kg (rat)
(ethylbenzene)
Dermal, LD50: 1100 mg/kg (Rabbit)
Inhalative, LC50/4h: 17,2 mg/l (rat)
(ethylbenzene)
Inhalative, LC50/4H: 27,6 mg/l (rat)

*

*

*

*

108-65-6 2-methoxy-1-methylethyl acetate

Oral, LD50: 8500 mg/kg (rat)
Dermal, LD50: >5000 mg/kg (Rabbit)
Inhalative, LC50/4h: 35,7 mg/l (rat)

*

*

*

*

- Hydrocarbons, C9-C12, n-alkanes, isoalkanes,

*

*

*

*

cyclics, aromatics (2-25%)

Oral, LD50: 15000 mg/kg (rat)
Dermal, LD50: 3400 mg/kg (rat)
Inhalative, LC50/4h: 13,1 mg/l (rat)

- Primary irritant effect:

• Skin corrosion/irritation
Irritant to skin and mucous membranes.
Causes skin irritation.

• Serious eye damage/irritation
Irritating effect.
Causes serious eye irritation.

• Respiratory or skin sensitisation
No sensitizing effects known.

• **STOT-single exposure**

May cause respiratory irritation.
May cause drowsiness or dizziness.

• **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

• **Practical knowledge**

Other observations:

Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the renal and central nervous systems. Symptoms include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause irritation and reversible local damage.

(continued on page 9)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number: 19460204

Reviewed on: 26.03.2025

Page : 9 / 12

PRODUCT : senotherm® Ofenspray 400ml gußgrau 17-1644-704206

(continued of page 8)

General comment:
There is no data available on the product itself.

12 Ecological information

There is no data available on the product itself. The product should not to be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

- **Aquatic toxicity:**
No further relevant information available.
- **12.2 Persistence and degradability**
No further relevant information available.
- **Behaviour in environmental systems:**
- 12.3 Bioaccumulative potential
No further relevant information available.
- 12.4 Mobility in soil
No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- PBT:
Not applicable.
- vPvB:
Not applicable.
- **12.7 Other adverse effects**
No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation
After prior treatment product has to be landfilled or incinerated adhering to the regulations pertaining to the disposal of especially hazardous waste. Do not allow into drains or water courses or dispose of where ground or surface waters may be effected.
- **Uncleaned packaging:**
- Recommendation:
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

- **14.1 UN-Number**
- .ADR UN1950
- .IMDG UN1950
- .IATA UN1950
- **14.2 UN proper shipping name**
- .ADR 1950 AEROSOLS
- .IMDG AEROSOLS
- .IATA AEROSOLS, FLAMMABLE
- **14.3 Transport hazard class(es)**
- .ADR
- .Class 2 Gases.

(continued on page 10)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number: 19460204

Reviewed on: 26.03.2025

Page : 10 / 12

PRODUCT : senotherm® Ofenspray 400ml gußgrau 17-1644-704206

(continued of page 9)

. Label

2.1



. IMDG

. Class

2.1

. Label

2.1



. IATA

. Class

2.1

. Label

2.1



• **14.4 Packing group**

. ADR

-

. IMDG

-

. IATA

-

• **14.5 Environmental hazards:**

Not applicable.

• **14.6 Special precautions for user**

Warning: Gases.

. Danger code (Kemler):

23

. EMS Number:

F-D,S-U

• **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

• **Transport/Additional information:**

Not applicable.

. Excepted quantities (EQ):

E0

. Limited quantities (LQ)

1L

. Transport category

2

. Tunnel restriction code

D

. IMDG

. Limited quantities (LQ)

1L

. Excepted quantities (EQ)

E0

• **UN "Model Regulation":**

UN 1950 AEROSOLS, 2 (2.1)

GB

(continued on page 11)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number: 19460204

Reviewed on: 26.03.2025

Page : 11 / 12

PRODUCT : senotherm® Ofenspray 400ml gußgrau 17-1644-704206

(continued of page 10)

15 Regulatory information

• **National regulations:**

- Technical instructions (air):
- Class Share in %
 - * III 22,76
 - I 0,01
 - II 0,02
- Waterhazard class:
Water hazard class 2 (Self-assessment): hazardous for water.
- * • **Poisons Act**
- * • Regulated explosives precursors
None of the ingredients is listed.
- * • Regulated poisons
None of the ingredients is listed.
- * • Reportable explosives precursors
67-64-1 acetone
- * • Reportable poisons
None of the ingredients is listed.
- * • **15.2 Chemical safety assessment:**
A Chemical Safety Assessment has not been carried out.

16 Other information

- The information contained in this safety data sheet is provided in accordance with the requirements of the CHIP regulation. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the suppliers's control, the user is responsible for ensuring that the requirements of relevant legislation
- * are complied with. The information contained in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance of health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitable for particular applications. Safety datasheet according to Regulation (EU) 2020/878.
 - * • **Relevant phrases**
 - * H220 Extremely flammable gas.
 - * H225 Highly flammable liquid and vapour.
 - * H226 Flammable liquid and vapour.
 - * H280 Contains gas under pressure; may explode if heated.
 - * H304 May be fatal if swallowed and enters airways.
 - * H312 Harmful in contact with skin.
 - * H315 Causes skin irritation.
 - * H318 Causes serious eye damage.
 - * H319 Causes serious eye irritation.
 - * H332 Harmful if inhaled.
 - * H335 May cause respiratory irritation.
 - * H336 May cause drowsiness or dizziness.
 - * H372 Causes damage to organs through prolonged or repeated exposure.
 - * H373 May cause damage to organs through prolonged or repeated exposure.
 - * H411 Toxic to aquatic life with long lasting effects.
 - * EUH066 Repeated exposure may cause skin dryness or cracking.

(continued on page 12)

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number: 19460204

Reviewed on: 26.03.2025

Page : 12 / 12

PRODUCT : senotherm® Ofenspray 400ml gußgrau 17-1644-704206

(continued of page 11)

- **Department issuing MSDS:**
Product safety department.
- **Contact:**
Tel. +49 (0) 6471 315 177 Fax +49 (0) 6471 315 5177 email: SDS-Info@weilburger.com
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
- *** Data compared to the previous version altered.**