

ToLEDo GLS

ToLEDo GLS V7 1920LM 840 E27 SL

0029597



Product features

- Compact and elegant design Suitable replacement for halogen, incandescent and compact fluorescent lamps Instant light at the flick of a switch Uniform light distribution Good colour rendering (CRI 80) Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas Lower maintenance costs 15,000 hours average rated life



PRODUCT OVERVIEW

Product name	ToLEDo GLS V7 1920LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	16.0
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Education, Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740989
Warranty	3 years
Luminous flux (lm)	1920
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Wattage (W)	16.0
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288295978

DATA TABLE

General data

Product name	ToLEDo GLS V7 1920LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	16.0
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open

ToLEDo GLS

ToLEDo GLS V7 1920LM 840 E27 SL

0029597

General application	Education, Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740989
Warranty	3 years

Optical data

Luminous flux (lm)	1920
Luminous flux (Rated) (lm)	1920
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	16.0
Equivalent watt (W)	120
Control gear required	No
No. Of switching cycles before premature failures	>50000
Dimmable	No
Inrush Current (A)	2.5
Inrush Duration (µs)	3600
Lamp Energy Label (class)	E
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	143
Nominal Product Diameter (mm)	67
Weight (kg)	0.083

Packaging

Single packaging type	Carton
Product EAN number	5410288295978
Packaging single length / height (cm)	13.2
Packaging single width (cm)	6.8
Packaging single depth (cm)	6.8
DUN14 (outer)	15410288295975
Units per outer package	6
Packaging outer length / height (cm)	14.0

ToLEDo GLS

ToLEDo GLS V7 1920LM 840 E27 SL


0029597

Packaging outer width (cm)	21.2
Packaging outer depth (cm)	14.3


Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS



SYLVANIA

ToLEDo GLS


ToLEDo GLS V7 1920LM 840 E27 SL

0029597



SYLVANIA

0029597



16
kWh/1000h



2019/2015

SYLVANIA


ToLEDo GLS

ToLEDo GLS V7 1920LM 840 E27 SL

0029597



0029597



16
kWh/1000h



2019/2015