

PRODUCT DATASHEET

L 4 W/640

Basic T5 Short | Tubular fluorescent lamps 16 mm, short, with G5 base



Areas of application

- Shops
- Supermarkets and department stores
- Public buildings

Product benefits

- Ideal for cost-effective creative illumination and decoration




TECHNICAL DATA

Electrical data

Nominal wattage	4 W
Construction wattage	4.60 W
Nominal voltage	29 V
Nominal current	0.17 A

Photometrical data

Luminous flux	140 lm
Luminous efficacy	30 lm/W
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥60
Light color	640
Rated LLMF at 2,000 h	0.80
Rated LLMF at 4,000 h	0.73
Rated LLMF at 6,000 h	0.69



349629_FL_640

Dimensions & Weight

Overall length	150.10 mm
Length with base excl. base pins/connection	136,00 mm
Diameter	16.00 mm
Tube diameter	16 mm
Product weight	14.62 g

Lifespan

Service life	4500 h
--------------	--------

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.92
Rated lamp survival factor at 6,000 h	0.50
Lifespan B50	6000 h

Additional product data

Base (standard designation)	G5
Mercury content	2.9 mg

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Energy efficiency class	G
Energy consumption	5.00 kWh/1000h

Country-specific categorizations

ILCOS	FD-4/640-E-G5-16/136
Order reference	L 4W/640

Energy labelling regulation data acc EU 2019/2015




Lighting technology used	OTHER_FL
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G5
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	150.10 mm
Height	16.00 mm
Width	16.00 mm
Chromaticity coordinate x	0,380
Chromaticity coordinate y	0,394


Beam angle correspondence	SPHERE_360
EPREL ID	546304
Model number	AC34071

Safety advice

– In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4077894-EN-00 - T5 SHORT
	Certificates	EAC RU C-DE HA10.B.00671 16 08 2018 15 07 2023 Expert Sertifikaciya FL
	Certificates	EAC N RU D-DE.MU62.B.00801_20 02.03.2020-01.03.2025 Prommash Test - FL

Photometric and lighting design files		Document name
	Spectral power distribution	349629_FL_640

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321025036	Sleeve 1	154 mm x 19 mm x 19 mm	20.90 g	0.06 dm ³
4008321062765	Folding box 10	98 mm x 41 mm x 155 mm	174.11 g	0.62 dm ³
4008321025043	Shipping box 10	166 mm x 105 mm x 51 mm	267.00 g	0.89 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.