

# Start Flood Flat IP65 1000LM 840 White

Item No: 0050108


**SYLVANIA**



The streamlined, durable, lightweight die-cast aluminium body makes Start Flood Flat a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. White (RAL9003) housing, white reflector, 1000 lm, 9 W, 111 lm/W, 4000K, non dimmable, CRI>80, IP65, IK06, Class I, lifespan L70:B50: 90000 hrs, 100 x 105 x 23 mm (L x W x H). Weight: 0.32kg.


## Technical Assets

### Dimensions (mm)



### Photometrics

Distance [m]	Cone diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	1.48	E10°	1610
	1.22	E10°	141
1.0	2.97	E10°	402
	2.43	E10°	38
1.5	4.45	E10°	179
	3.65	E10°	16
2.0	5.93	E10°	101
	4.87	E10°	9
2.5	7.41	E10°	64
	6.09	E10°	6
3.0	8.90	E10°	45
	7.50	E10°	4



# Start Flood Flat IP65 1000LM 840 White

Item No: 0050108

**SYLVANIA**

## General data

Product name	Start Flood Flat IP65 1000LM 840 White
Technology	LED
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC001744
E-number FI	4579545
Warranty	3 years

## Optical data

Useful luminous flux ( $\Phi_{use}$ )	1000
Fixture luminous flux (lm)	1000
Luminaire efficacy (lm/W)	111
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	110
Photobiological Risk Group	RG1

## Electrical data

Total power consumption (W)	9
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
Drive current (mA)	19
Inrush Current (A)	18
Inrush Duration ( $\mu$ s)	125
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	17
Max. products per 13A C Breaker	22
Max. products per 16A C Breaker	28
Max. products per 20A C Breaker	34
Max. products per 10A B Breaker	10
Max. products per 13A B Breaker	13
Max. products per 16A B Breaker	17
Max. products per 20A B Breaker	21

## Lifetime data

Lifespan L70 B50	90000
Lifespan L80 B50	85000
Lifespan L80 B20	54000

# Start Flood Flat IP65 1000LM 840 White

Item No: 0050108

**SYLVANIA**

## Physical data

Housing colour	White
IP rating	IP65
IK rating	IK06
Nominal Product Length (mm)	100
Nominal Product Width (mm)	105
Nominal Product Height (mm)	23
Weight (kg)	0.32

## Packaging

Product EAN number	5410288501086
Packaging single length / height (cm)	13.0
Packaging single width (cm)	5.5
Packaging single depth (cm)	15.5
DUN14 (inner)	15410288501083
Units per outer package	6
Packaging outer length / height (cm)	36.0
Packaging outer width (cm)	14.5
Packaging outer depth (cm)	17.5

## Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40