

Product data sheet

Item No. 91.207.1004.2

Cable assembly GST15I4KS-SX15 V 10WS

geis® Connection cable male - free end; length: 1m; type GST15I4; 4-pole; 250/400 V / 16 A; colour of coding: white with white strain-relief; cable: H05VV-F 4G1,5, colour: white



Item No.	91.207.1004.2
EAN	4015573953376
Order Unit	50 Piece(s)

Certificates / Approvals

Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	White
Marking of poles	
Color of housing inclusive strain relief	White

Model

Number of poles	4
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP40
Wire strip length	8 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F
Cable colour	White
Cable diameter	9.2 mm

Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST15i4 plug
Version cable end 2	Free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	1 m
--------------	-----

Technical drawing

		<table border="1"> <tr> <th>.F</th> <th>Farbe colour</th> <th>Pos.1</th> <th>Pos.2</th> <th>Codierung y</th> </tr> <tr> <td>.2</td> <td>weiß white</td> <td>91.942.3053.0</td> <td>00.100.0202.2 Farbe: weiß colour: white</td> <td>2 1 PE N</td> </tr> </table>	.F	Farbe colour	Pos.1	Pos.2	Codierung y	.2	weiß white	91.942.3053.0	00.100.0202.2 Farbe: weiß colour: white	2 1 PE N					
.F	Farbe colour	Pos.1	Pos.2	Codierung y													
.2	weiß white	91.942.3053.0	00.100.0202.2 Farbe: weiß colour: white	2 1 PE N													
Gesamtlänge / total length		<table border="1"> <tr> <th colspan="5">Anschlußbelegung/pole assignment</th> </tr> <tr> <th>Polekennzeichnung/N</th> <th>PE</th> <th>1</th> <th>2</th> <th></th> </tr> <tr> <td>Aderfarbe/ wire color</td> <td>bl</td> <td>gr/ge</td> <td>br</td> <td>sw</td> </tr> </table>	Anschlußbelegung/pole assignment					Polekennzeichnung/N	PE	1	2		Aderfarbe/ wire color	bl	gr/ge	br	sw
Anschlußbelegung/pole assignment																	
Polekennzeichnung/N	PE	1	2														
Aderfarbe/ wire color	bl	gr/ge	br	sw													
Weitere Daten siehe Katalog further data see catalog		<table border="1"> <tr> <th>Teile-Nr. part-no.</th> <th>L</th> <th>Beispiel (Farbe: weiß) example (colour: white)</th> <th>Typ type</th> </tr> <tr> <td>91.207.XX04.2</td> <td>XX in dm-Schritten</td> <td>91.207.1004.2 = 10dm/L= 1000mm</td> <td>GST15i4KS-S 15 10WS</td> </tr> <tr> <td>U1.207.XX04.2</td> <td>XX in m-Schritten</td> <td>U1.207.1204.2 = 12 m/L=12000mm</td> <td>GST15i4KS-S 15 X12WS</td> </tr> </table>	Teile-Nr. part-no.	L	Beispiel (Farbe: weiß) example (colour: white)	Typ type	91.207.XX04.2	XX in dm-Schritten	91.207.1004.2 = 10dm/L= 1000mm	GST15i4KS-S 15 10WS	U1.207.XX04.2	XX in m-Schritten	U1.207.1204.2 = 12 m/L=12000mm	GST15i4KS-S 15 X12WS			
Teile-Nr. part-no.	L	Beispiel (Farbe: weiß) example (colour: white)	Typ type														
91.207.XX04.2	XX in dm-Schritten	91.207.1004.2 = 10dm/L= 1000mm	GST15i4KS-S 15 10WS														
U1.207.XX04.2	XX in m-Schritten	U1.207.1204.2 = 12 m/L=12000mm	GST15i4KS-S 15 X12WS														
Typ/type: GST15i4KS-S 15 .. WS = weiß/white																	
Anwendung/application: Netzanschluß/mains connection																	
Toleranz nach DIN 9137/Tolerance system acc. to DIN 9137. This DIN-standard describes the envelope principle. According to the envelope principle the deviations of form and position are limited by the size tolerances.																	
Zeichnung nach DIN 9137/Drawing according to DIN 9137. This DIN-standard describes the envelope principle. According to the envelope principle the deviations of form and position are limited by the size tolerances.																	
General tolerance																	
CD - Drawing, no manual modifications allowed																	
First Use																	
Zeichnung Nr./Drawing No.																	
91.207.0204.2 01K																	
Made in mm/Dimensions are in mm																	
Wieland																	
INSTALL. COUPLER KONFEKT-LEITUNG																	
Stecker/male-frees Ende/free end 1,50mm																	
Schraubanschluß/screw connection KS 250V/400																	
90-PEH/08/91																	