

Product data sheet

Item No. 91.207.3063.2

Cable assembly GST15I4KSB-X15HV 30WS

geis® Connection cable female - free end; length: 3m; type GST15I4; 4-pole; 250/400 V / 16 A; colour of coding: white with white strain-relief; cable: H05Z1Z1-F 4G1,5 , colour: white



Item No.	91.207.3063.2
EAN	4049644010217
Order Unit	20 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	White
Marking of poles	
Color of housing inclusive strain relief	White

Model

Number of poles	4
Nominal cross section conductor	1.5 mm²
Degree of protection (IP)	IP40
Wire strip length	8 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05Z1Z1-F

Cable colour	White
Cable diameter	9.2 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	GST15i4 socket
Version cable end 2	Free end

Material

Surface finish	Silver-plated
Halogen free	Yes
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	3 m
--------------	-----