

10429500	DATA SHEET	
Valid from: 21.08.2026	EPIC® H-A 3 MTGVB	

Description

- Innovative metal housing
- For safe connections in the smallest possible space

General characteristics

Series	H-A 3
Version	Cable coupler hood
Locking mechanism	Single lever
Cable entry	Straight
Cable gland	See table
Clamping range	See table
Protection rating (DIN EN 60529)	IP 66 (latched) IP 68 - 1 meter / 10 hours (latched)
Temperature range	-40 °C to +125 °C



Materials and surfaces

Housing, base material	Zinc die-casting
Housing, surface	Powder-coating, grey
Pressure screw	Brass, nickel-plated
Pressure washer	Steel, zinc-plated
Incised sealing ring	NBR
Lever	PA

Standards

Safety Standard	IEC 61984
-----------------	-----------


Versions

Article number	Article description	Thread	Cable gland	Clamping range
19512900	EPIC® H-A 3 MTGVB M20 N.GEW. CABLE COUPLER HOOD	M20	No	-
19429500	EPIC® H-A 3 MTGVB M20 KPL. CABLE COUPLER HOOD	M20	Yes	3 – 13,5 mm

Creator: TOB01/PDP Released: TODV1/PDP	Document: DB10429500EN Version: 03	Page 1 of 2
---	---------------------------------------	-------------

10429500	DATA SHEET	
Valid from: 21.08.2026	EPIC® H-A 3 MTGV	

Technical Drawings



Industrial machinery and plant engineering



Mechanical resistance



Robust



Waterproof

Info

Compact, robust metal housings size H-A 3

Application range

Machine and equipment manufacturing
Control engineering
Electronic laboratory

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: TOB01/PDP Released: TODV1/PDP	Document: DB10429500EN Version: 03	Page 2 of 2
---	---------------------------------------	-------------